USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	Fraction	C/5E	1 4 6	number	Township number S R Range number	
2. Distance and direction from nearest town or city: 2. Distance and direction from nearest town or city: 3. Distance and direction from nearest town or city: Street address of well location if in city:		3. R.	Owner of well	-//	loyd Rose Northridge D	
4. Locate with "X" in section below:	Sketch map:		ity, state, zip d	ode:	6. Bore hole dia. 29 in. Completion date	_
NW NE					7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotar	ту
E E				8. Use: Domestic Public supply Industry 'Irrigation Air conditioning Stock Lawn Oil field water Other		
sw sx s				9. Casing: Material JCC/ Height: Above or below Threaded Welded Surface in RMP PVC Weight lbs./f	1. t.	
1 Mile ———			From	То	Dia. in. to 16.7 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No	_
5. Type and color of material			From	10	10. Screen: Manufacturer's name	_
Sandy Jop Son	<u>L</u>		0	2	Type 5/ce/ Dia. /6	_
Brown Clay			2	8		- 1.
Redish Brown	Clay		8	57	Gravel pack? Size range of material 1/2 3/4 3/1	É
Sandy Clay			57	6	11. Static water level: mo./day/yi	L
Sand & Shavel	Clay	Mines	061	89	12. Pumping level below land surfaces: 66 ft. after 2 hrs. pumping 2000g.p.m	
Brown Clay	<i></i>		89	106	ft. after hrs. pumping g.p.m	
Fine sand de	24 M	Uneo	v 106]//	Estimated maximum yield	· .
Sand & Shavel			///	147	14. Well head completion:	
Brown Clay			147	167	Pitless adapter Inches above grade 15. Well grouted?	1.5
Comented San	l		167	200	With: Neat cement Bentonite Concrete Depth: FromO ft. toO ft.	$\begin{bmatrix} 1 & 1 & 7 \\ 1 & 1 & 6 \end{bmatrix}$
					16. Negrest source of possible contamination: ft Direction Type CLYTTE Well disinfected upon completion? Yes N	- lo
					17. Pump: Not installed Manufacturer's name 14/68	7 / 7
					Model number $\frac{5CH}{12}$ HP $\frac{100}{12}$ Volts Length of drop pipe $\frac{145}{12}$ ft. capacity $\frac{120}{12}$ g.p.m	
					Type: SubmersibleTurbine	1.3
(Use a second s	heet if needed)				Jet Reciprocating Other	[S P
18. Elevation: 19. Remarks:				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report		
-				is true to the best of my knowledge and belief.		
Topography: Hill					Rosencyantz - Bom's 134 Business names License No	
Slope Upland					Address Dead Bend, 85.	- <u>z</u> O
Valley					Authorized representative Date Lag	