

1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 NE 1/4 Section Number 1 Township Number T 27 S Range Number R 16 E  
 County: KIOWA

Distance and direction from nearest town or city street address of well if located within city?  
WELLSFORD 1/2 E 7 3/4 N WESTSIDE

2 WATER WELL OWNER: STERLING DRILLING CO. Board of Agriculture, Division of Water Resources  
 RR#, St. Address, Box # : BOX 129 Application Number:  
 City, State, ZIP Code : STERLING KS 67579

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	E
S	SW	SE	

4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 40 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr 10-1-81  
 Pump test data: Well water was     ft. after     hours pumping     gpm  
 Est. Yield     gpm: Well water was     ft. after     hours pumping     gpm  
 Bore Hole Diameter: 9 in. to 70 ft. and     in. to     ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes     No    ; If yes, mo/day/yr sample was submitted      
 Water Well Disinfected? Yes     No    

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped      
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded      
 7 Fiberglass Threaded      
 Blank casing diameter: 5 in. to 50 ft., Dia.     in. to     ft., Dia.     in. to     ft.  
 Casing height above land surface: 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 2-14  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)      
 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 1/8  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)      
 SCREEN-PERFORATED INTERVALS: From 5.0 ft. to 70 ft., From     ft. to     ft.  
 From     ft. to     ft., From     ft. to     ft.  
 GRAVEL PACK INTERVALS: From 40 ft. to 70 ft., From     ft. to     ft.  
 From     ft. to     ft., From     ft. to     ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other      
 Grout Intervals: From 0 ft. to 10 ft., From     ft. to     ft., From     ft. to     ft.  
 What is the nearest source of possible contamination: NONE  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage

Direction from well?			How many feet?		
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
<u>0</u>	<u>8</u>	<u>SAND</u>			
<u>8</u>	<u>40</u>	<u>SAND CLAY</u>			
<u>40</u>	<u>70</u>	<u>GRAVEL</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-1-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 10-17-81 under the business name of PELSEY WATER WELL SERVING by (signature) Pelley J. Pelley

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
T 27 R 16 E 1/4 NE 1/4 NW 1/4