WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well: KIOWA SWI/4 NEI/4 NW/4 24 T 27 S R 7W EM 2. Distance and direction from nearest town or city: 5N 4/34 W Street address of well location if in city: OF HAVILAND, KS City, state, zip code: HAVILAND; KANSAS 4. Locate with "X" in section below: Sketch map: Well depth 175 ft. Coble tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotar 8. Use: Domestic Public supply Industry K Irrigation Air conditioning Stock Well water Other 9. Casing: Material STL Height: Above below Threaded Welded N Surface 12 in RMP PVC Weight SZ2 7 lbs./ft CLY, Rotar SANDY 2 20 Set between 1/5 ft. and 125 ft. Sold SANDY SAND, FINATO COARS & MISTO GALL STLEAKS 20 89 Gravel pack? X Size range of material 12 X Stleaks 20 89 Gravel pack? X Size range of material 12 X Stleaks 30 Size
Street address of well location if in city: OF HAVILAND, K5 R.R. or street: City, state, zip code: HAVILAND, KANSAS 6. Bore hole dia. 30 in. Completion date Well depth 175 ft. /Z FULL TS Well depth 175 ft. /Z FULL TS 7Coble tool _Rotory _Driven _Dug
Street address of well location if in city: OF HAVILAND, LS City, state, zip code: HAVILAND, LANSAS 6. Bore hole dia. 30 in. Completion date Well depth 175 ft. 7. Coble toolRotaryDrivenDug Hollow rodJettedBored X Reverse rotar 8. Use:DomesticPublic supplyIndustry X IrrigationAir conditioningStock
4. Locate with "X" in section below: Sketch map: 6. Bore hole dia. 30 in. Completion date Well depth 175 ft. 7. Coble tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotar 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material ST Height: Bore below Threaded Welded X Surface 12 in RMP PVC Weight 32.7 lbs./ft Dia. in. to 15 ft. depth Wall Thickness: inches or Dia. in. to ft. depth Wall Thickness: inches or Dia. in. to ft. depth lagge No. 188 10. Screen: Manufacturer's name SAND, FINE TO COARS & MED GRAY & CLAY STEAKS 20 89 Gravel pack? X Size range of material Is Static water level: 11. Static water level: 12. Static water level: 13. Static water level: 14. Static water level: 15. Static water level: 16. Bore hole dia. 30 in. Completion date Well depth 175 ft. 2
7Cable toolRotaryDrivenDugHollow rodJettedBared X Reverse rotar
Hollow rodJettedBored X Reverse rotar 8. Use:DomesticPublic supplyIndustry
Sand, Fing To Coals of Mest Gray & Clay Steaks 20 89 Sirigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material STL Height: Bow or below Threaded Welded X Surface 12 in RMP PVC Weight 32.7 lbs./fi Dia La in. to L5 ft. depth Wall Thickness: inches or Dia. in. to ft. depth lyage No. 188 10. Screen: Manufacturer's name WA Brown N Type These To Dia. 16 Set between 15 ft. and 175 ft. Gravel pack? X Size range of material 18 XX
LawnOil field waterOther
Threaded Welded X Surface 12 in RMP PVC Weight 32.7 lbs./fi Soul Sand Sand Sand From To Dia. in. to 15 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 188 10. Screen: Manufacturer's name WA BROWN Type Flor Flo Dia. 16 Slot/gauze 18 Length 60 Set between 1/5 ft. and 175 ft. and
RMP PVC Weight 32.7 lbs./fi 1 mile 1 5. Type and calor of material From To Dia. in. to ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 188 10. Screen: Manufacturer's name BROWN Type Flore Flo Dia. 16 Slot/gauze /8 Length 60 Set between 1/5 ft. and 175 ft. SAND, FING TO COARS & METO GRAY & CLAY STRANS 20 89 Gravel pack? Size range of material 18 X 36 To Static water level: me. /day/rr
5. Type and calor of material From To Diain. toft. depth gage No/88 10. Screen: Manufacturer's name WA BROWN Type Flore Flo Dia. 16 Slot/gauze /8 Length 60 Set between //5 ft. and /75 ft. SAND, FINE TO COARS & METO GRAY & CLAY STREAKS 20 89 Gravel pack? A Size range of material 18 X 36 Gravel pack? A Size range of material 18 X 36 To Diain. toft. depth gage No/88 Type Flore Flo Dia. 16 Set between //5 ft. and /75 ft. Gravel pack? A Size range of material 18 X 36 The static water level:
SOUL, SANDY O 2 Type Flor Flo Dia. 16 Slot/gauze /8 Length 60 Set between 1/5 ft. and 175 ft. Gravel pack? A Size range of material 18 X 36 To Coal Sand Coal Sa
SAND, FINE TO COARS & MED GREY & CLAY STREAKS 20 89 Gravel pack? X Size range of material 18 X 36
SAND, FINE TO COARS & METO GRAY & CLAY STREAKS 20 89 Gravel pack? X Size range of material 18 X 36
SAND, FINE TO COARS & MED GRY & CLAY STREAKS 20 89 Gravel pack? X Size range of material 18 X36
11. Static water level: ma./day/yr
DAND, FINETO GARSE & MED GRAVEL 87 93 28 ft. below land surface Date 12 July 19
CIAL, TAN 93 103 12. Pumping level below land surfaces: 40 ft. ofter hrs. pumping 800 g.p.m
SIND. FUE TO COARSE & CORRES GROWEL 103 117 43 ft. ofter - hrs. pumping / 000 g.p.m
Estimated maximum yield
SAND, FINS TO COLLYS of CORES GRAVEL 171 175 14. Well head completion: 12
Pitless adapter 12 Inches above grade
15. Well grouted? X 102 172 With: Neat cement X Bentonite Concrete
SHALE, BLACK 192 220 With: Neat cement & Bentonite Concrete Depth; From 6 ft. to 10 ft.
16. Nearest source of possible contamination: ft Direction Type NONE
Well disinfected upon completion? YesN
17. Pump: Not installed Monufacturer's name Simnous
Model number Sm 13 HP Volts
Length of drop pipe \(\square \text{100} \) ft. capacity \(\square \text{100} \) Type:
Submersible X Turbine Reciprocating
(Use a second sheet if needed) Centrifugal Other
18. Elevation: 19. Remarks: 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report
is true to the best of my knowledge and belief.
Topography: Hill Doured of Surface Business name License No
Slope Address 1221 N. MAIN PROTT
Vigland Signed Thannih Date Aug