WATER WELL REC	ORD	Form WWC-5	Division of Water Resources App. No.			
1 LOCATION OF WAT			Section Number	I ownsnip No.	Range Number	
County: Kiowa		SW 1/4 SW 1/4 1/4	28		R 17 □E K W	
Street/Rural Address of	Global Positioning					
from nearest town or int	Latitude: (in decimal degrees)					
3N of Greensburg, KS			Longitude: (in decimal degrees)			
2 WATER WELL OWNER: Roger Yost			Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 8266 Hwy 183			GPS unit (Make/Model:)			
City, State, ZIP Code	: Greensburg,	KS 67054-4708	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL						
SECTION BOX:	Depth(s) Groundwater Er	countered (1)48	ft. (2)	ft.	(3) ft.	
	WELL'S STATIC WATER LEVEL48ft. below land surface measured on mo/day/yr 03/22/10					
Pump test data: Well water wasft. after						
EST. YIELD. 70 gpm. Well water was ft. after hours pumping g						
W E Bore Hole Diameterin. toft., andin. toft.						
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)						
I Improvious Tandrotain Domentic lorum & control Tandrotain and						
X						
S If yes, mo/day/yr sample was submitted						
1 mile Water well disinfected? ☑ Yes ☐ No						
5 TYPE OF CASING USED: Steel X PVC Other						
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to 88 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 12 in., Weight 2.8 lbs./ft., Wall thickness or gauge No. Sch. 40						
Casing diameter						
Casing height above land surface						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
Steel Stainless Steel NPC Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From88 ft. to108 ft., From ft. to ft.						
From						
GRAVEL PACK INTERVALS: From						
From						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Grout Intervals: From						
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)						
Sewer lines	wage lagoon Fuel storage					
Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well						
Direction from well Eas.t. Distance from well 117.						
FROM TO	LITHOLOGIC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	JGGING INTERVALS	
	nd		V	20		
12 35 clay	-		Yost 1-2			
	nd gravel			D		
65 75 clay				Drilling C	ompany	
75 108 sand ar	nd gravel		PO Box 1			
			Pratt, K	S 67124		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year)03./22/10 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No186 This Water Well Record was completed on (mo/day/year) 04/10/10						
under the business name ofKelly.'sWaterWell .Service Inc by (signature)Kattum						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Der	partment of Health and Enviro	nment, Bureau of Water, Geolo	gy Section, 1000 SW Jac	kson St., Suite 420,	Topeka, Kansas 66612-1367.	
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212	mgca.littiii.					