

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: County: Kiowa, Fraction 1/4 NE 1/4 SE 1/4 SE 1/4, Section Number 11, Township No. T 27 S, Range Number R 17 E W. Street/Rural Address of Well Location: 5 3/4 North, 1 3/4 West of Haviland. 2 WATER WELL OWNER: Mull Farms & Feeding, RR#, Street Address, Box #: 553 R Road, City, State, ZIP Code: Pawnee Rock, Ks. 67567. Global Positioning System (GPS) information: Latitude, Longitude, Elevation, Datum, Collection Method.

3 LOCATE WELL WITH AN "X" IN SECTION BOX: Diagram showing a 2x2 grid with 'X' in the SE quadrant. 4 DEPTH OF COMPLETED WELL 115 ft. Depth(s) Groundwater Encountered (1) 55 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 55 ft. below land surface measured on mo/day/yr. 7-18-12. Pump test data: Well water was... ft. after... hours pumping... gpm. EST. YIELD. N/A... gpm. Well water was... ft. after... hours pumping... gpm. Bore Hole Diameter 10 in. to 11.5 ft. and... in. to... ft. WELL WATER TO BE USED AS: Public water supply, Geothermal, Injection well, Domestic, Feedlot, Oil field water supply, Dewatering, Other (Specify below) Stock, Irrigation, Industrial, Domestic-lawn & garden, Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes No. If yes, mo/day/yr sample was submitted... Water well disinfected? Yes No.

5 TYPE OF CASING USED: Steel PVC Other. CASING JOINTS: Glued Clamped Welded Threaded. Casing diameter 5 in. to 11.5 ft., Diameter... in. to... ft., Diameter... in. to... ft. Casing height above land surface 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify), Brass Galvanized Steel None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole), Louvered shutter Key punched Wire wrapped Saw cut Other (specify). SCREEN-PERFORATED INTERVALS: From 115 ft. to 100 ft., From... ft. to... ft., From... ft. to... ft. GRAVEL PACK INTERVALS: From 115 ft. to 20 ft., From... ft. to... ft., From... ft. to... ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other. Grout Intervals: From... ft. to... ft., From 20 ft. to 0 ft., From... ft. to... ft. What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below), Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well, Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well None. Direction from well... Distance from well...

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-2 Top soil, 2-31 Clay, 31-115 Sand & gravel.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 7-18-12 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134. This Water Well Record was completed on (mo/day/year) 8-21-12 under the business name of Rosencrantz-Bemis by (signature) Sara Reep.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.