


(dri)

1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 34 Township Number T 27 S Range Number R 18 E 0
 County: Riowa

Distance and direction from nearest town or city street address of well if located within city?
3 1/2 N of Greensburg

2 WATER WELL OWNER: Don Unruh
 RR#, St. Address, Box #: R+1 Box 112B Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Greensburg, KS 67054 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 180 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 46 ft. 2. 46 ft. 3. 5-22-99 ft.
 WELL'S STATIC WATER LEVEL 46 ft. below land surface measured on mo/day/yr 5-22-99
 Pump test data: Well water was 46 ft. after 50 gpm; Well water was 834 ft. after 100 gpm
 Est. Yield 50 gpm; Well water was 834 ft. after 100 gpm
 Bore Hole Diameter 8 3/4 in. to 100 in. to 100 in. to 100 in.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 10060 ft., Dia 24 in. to 20016 lbs./ft. Wall thickness or gauge No. 20016
 Casing height above land surface 24 in., weight 20016 lbs./ft.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 6 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 10 ft. to 100 ft., From 10 ft. to 100 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 100 ft., From 20 ft. to 100 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From top ft. to 20 ft., From 20 ft. to 100 ft., From 100 ft. to 100 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? _____ How many feet? _____

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	sandy topsoil			
10	25	sandy clay			
25	42	white clay			
42	75	sand + gravel			
75	76	white clay			
76	100	sand + gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 5-22-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 101 This Water Well Record was completed on (mo/day/yr) 5-25-99 under the business name of Bartel Well Drilling, Inc. by (signature) Reuben J. Bartel

OFFICE USE ONLY
T
R
EW
SEC.