


USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: County Knowa		Fraction 1/4c 1/4NW 1/4		Section number 25 4		Township number T 27 S R 18 E/W		Range number						
2. Distance and direction from nearest town or city: 5 3/4 south 1/4 west of Centerview, Ks.					3. Owner of well: Carl Simpson R.R. or street: Lewis, Ks. City, state, zip code:									
4. Locate with "X" in section below: 					Sketch map:					6. Bore hole dia. 29 in. Completion date 7-15-76 Well depth 148 ft.				
										7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary				
										8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other				
										9. Casing: Material steel Height Above of below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 18 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <input type="checkbox"/> lbs./ft. Dia. 16 in. to 148 ft. depth; Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth; gage No. 7 58				
5. Type and color of material					From		To		10. Screen: Manufacturer's name Doerra Type steel Dia. 16 Slot/gouze 3/16 Length 60 Set between 88 ft. and 148 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 3/4-3/8					
sandy top soil					0		3		11. Static water level 36' WL mo./day/yr. <input checked="" type="checkbox"/> ft. below land surface Date 4-15-76					
brown and yellow clay					3		9		12. Pumping level below land surfaces: 34 ft. after 1 hrs. pumping 1200 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 1300 g.p.m.					
brown clay with sand					9		19		13. Water sample submitted: mo./day/yr. <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Date 4-15-76					
brown clay					19		39		14. Well head completion: <input type="checkbox"/> Pitless adapter <input type="checkbox"/> Inches above grade					
sand and gravel brown clay					39		43		15. Well grouted? <input checked="" type="checkbox"/> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.					
sand and gravel					43		100		16. Nearest source of possible contamination: 2N Direction north Type septic tank Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No					
white rock					100		104 1/2		17. Pump: Manufacturer's name Jacuzzi Not installed Model number 4-12-LSHP 60 Volts <input type="checkbox"/> Length of drop pipe 80 ft. capacity 900 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other					
sand and gravel					104 1/2		111		(Use a second sheet if needed)					
brown clay and white rock					111		119							
sand and gravel					119		149 1/2							
hard brown clay					149 1/2		150 1/2							
18. Elevation:		19. Remarks:								20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Business name Rosencrantz-Bemis License No. 134 Address Great Bend, Ks Signed [Signature] Date 9/11/76 Authorized representative				

87
 18
 4
 C
 1/4
 1/4
 1/4
 1/4