WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Froction Center | l | Section | | Township number | Range number | | |
|---|-----------------|-----------------|-----|---------|---------|---|--|----------------|--|
| 1. Location of well: | Kiowa | 1/4 1/4 NE | 1/4 | | 7 | т 27 s | R 18 | ₽ ⊘ | |
| Distance and direction from nearest town or city: 3. Owner | | | | | II: Mic | 1-America Land C | 1 | | |
| 8½ miles Northwest of Greensburg, KS Streef address of well location if in city: Cas City, state, zip code Gre | | | | | | o Terry Gleason sterline Irrigat eensburg, KS 67 | | | |
| 4. Locate with "X" in section below: N | | | | | ĺ | 6. Bore hale dia. 24 in. Well depth 175 ft. | | <u>-27–</u> 78 | |
| NW 1 X | | | | | | 7Cable toolRotaryDrivenDugHollow rodJettedBoredXReverse rotary 8. Use:DomesticPublic supplyIndustryX_IrrigationAir conditioningStockLownOil field waterOther | | | |
| E E | | | | | | | | | |
| - SW SE I I I I I I I I I I I I I I I I I | | | | | | 9. Casing: Material steel Height: Above or below Threaded Welded Surface 12 in. RMP PVC Weight 30 . 3lbs./ft. | | | |
| 1 1 M | Aile ———— | | | | | Dia 16 in. to 80 ft. dep | th Wall Thickness: inc | hes or | |
| 5. Type and color of material | | | | From | То | Dia 16 in. to 135 ft. dept | | <u> </u> | |
| Top soil & sand | | | | 0 | 9 | Type Double-slot Dia. 16" Slot gauze 1/8 Length 80' Set between 80 ft. and 120 ft. 135 ft. and 175 ft. | | | |
| Sandy clay | | | | 9 | 19 | | | | |
| Sand & gravel | | | | 19 | 28 | Gravel pack? YES Size ran | nd175 nge of material 3/8- | 200 ft. | |
| Brown clay & sandstone | | | | 28 | 40 | 11. Static water level: mo./doy/yr. 41 ft. below land surface Date 4-27-78 | | | |
| Sand & gravel & clay streaks | | | | 40 | 58 | 12. Pumping level below lond | surfaces: N/C | | |
| Sand & gravel | | | | 58 | 77 | ft. after h | ors. pumping | g.p.m. | |
| Brown clay | | | | 77 | 83 | 13. Water sample submitted: | mo./ | /day/yr. | |
| Sand & gravel & lime streak at 114' | | | | 83 | 117 | Yes X No [| Date | | |
| Brown & gray clay & limestone | | | | 117 | 139 | Pitless adapter 1 15. Well grouted? yes | 2 Inches above g | | |
| Sand & gravel | | | | 139 | 175 | With: X Neat cement Depth: From ft. to | Bentonite Co | oncrete J | |
| | | | | | | 16. Nearest source of possible | contamination: FI | ELD | |
| | | | | | | Well disinfected upon comple | • | X_No | |
| | | | | | | 17. Pump: Manufacturer's name Pee | | ~ ^ | |
| | | | | | | Model number 12LB-2 Length of drop pipe 70 | HP <u>80</u> Volts ft. capacity <u></u> 900 | g.p.m. (€ | |
| | | | | | | Type: Submersible | X Turbine | | |
| | (Use a second s | neet if needed) | | | | Jet Centrifugal | Reciproc | ating S | |
| 18. Elevation: 19. Remarks: | | | | | | 20. Water well contractor's c | ertification: | eport | |
| Topography: | | | | | | is true to the best of my knowled Clarke Well & E | - | .85 \$(| |
| Hill Slope | | | | | | Business name Address Great Bend | Licer | nse Na. | |
| Upland | | | | | | Signed U-W Clarke Date Date | | | |
| Valley | | | | | i | Authorized repr | | <u> </u> | |