


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 26 Township Number T 27 S Range Number R 18 EW
 County: King

Distance and direction from nearest town or city street address of well if located within city?
1 East of Collinsburg 1/2 North East Into

2 WATER WELL OWNER: LOTOS OPERATING
 RR#, St. Address, Box #: 1005, Mdinst, Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Wichita, KS 67202 Application Number: 20060481

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 111 ELEVATION:
 Depth(s) Groundwater Encountered: 62 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 62 ft. below land surface measured on 12-18-06 mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 5 in. to 11 1/2 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 12 in., weight 160 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 8 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 111 ft. to 91 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 111 ft. to 24 ft., From ft. to ft.

6 GROUT MATERIAL: 24 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 24 ft. to 0 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Nothing on location
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Sand, Top Soil			
6	18	TAN Clay			
18	24	Fine Sand			
24	32	Tan Clay			
32	66	Fine Sand TAN			
66	84	Coarse Sand			
84	104	Coarse Sand (small gravel)			
104	111	Coarse Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-18-06 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's Licence No. 672 This Water Well Record was completed on (mo/day/yr) 12-18-06 under the business name of Crow's Water Well by (signature) [Signature]