		WWC-5		sion of Water	2014/119		
Original Record		ge in Well Use Fraction		urces App. No.		Well ID	
1 LOCATION OF W	Section Number Township Number Range Number						
		1/4 NW/4 NE		33	'T 27 S	R /8 □ E 🗷 W	
2 WELL OWNER: L		First:				(if unknown, distance and	
Business: Sterling Drilling Co.			direction from nearest town or intersection): If at owner's address, check here:				
Address: P.o.	From Gr	Then west to 29 Rd 5/8 mile North & G. S.E.					
City: PRA-17		5 ZIP: 67/24	Then we	57 70 Z	Ad 3/8 mile	. North & G. S.E.	
3 LOCATE WELL			To we				
WITH "X" IN	4 DEPTH OF COM	MPLETED WELL:	π.			(decimal degrees)	
SECTION BOX:	1 21 H 31 H 07 41			`			
N 2)							
□ balow land surface measured on (mo-day			(-1/r)	Source for Latitude/Longitude: GPS (unit make/model:)			
above land surface, measured on (mo-day			(-VI) 2-19-15	(V) $Z - 19 - 15$ $(WAAS enabled? \square Yes \square No)$			
Pump test data: Well water was			ft. Land Survey Topographic Map				
w E	after hours numping			Online Mapper:			
Well water was			ft.		• •		
SWSE after hours pumping			. gpm	6 Flovatio	m· ft	Ground Level G TOC	
	Estimated Yield:gpm		A 1	6 Elevation:ft. ☐ Ground Level ☐ TOC ft and Source: ☐ Land Survey ☐ GPS ☐ Topographic Map			
S Bore Hole Diameter: 105/8. in. to25			π. and				
7 WELL WATER TO		in. to	11.				
1. Domestic:		ater Supply: well ID		10 X Oil F	ield Water Supply: 1	ease UNruH 4-33	
☐ Household		ng: how many wells?					
☐ Lawn & Garden		Recharge: well ID					
☐ Livestock		ng: well ID		12. Geothermal: how many bores?			
2. Irrigation		tal Remediation: well I	D	· · · · · ·			
3. 🔲 Feedlot	☐ Air Sparg		Extraction	b) Open Loop Surface Discharge Inj. of Water			
4. 🔲 Industrial	☐ Recovery	☐ Injection		13.	r (specify):		
Was a chemical/bacter	riological sample subr	nitted to KDHE? 🗆	Yes 🔀 No	If yes, date sa	ample was submitte	ed:	
Water well disinfected?	Yes □ No		-				
8 TYPE OF CASING	USED: ☐ Steel X PV	C Other	CASIN	IG JOINTS: 🕽	🛚 Glued 🔲 Clampe	d ☐ Welded ☐ Threaded	
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter ft., Diameter ft., Diameter ft.							
Casing diameter	111. 10 10.	, Diameter	- 111. 10	It., Diamete	i III. 10	IL.	
Casing height above land	surface i	n. Weight	2 lbs./ft.	Wall thickne	ss or gauge No		
Casing height above land TYPE OF SCREEN OF	surface 2.4 i R PERFORATION MA	n. Weight 1.6.6 TERIAL:	2 lbs./ft.	Wall thickne	ss or gauge No		
Casing height above land TYPE OF SCREEN OI ☐ Steel ☐ Stai	surface Z.Y i R PERFORATION MA nless Steel ☐ Fibe	n. Weight 16.6 ATERIAL: arglass ▼ PVC	2 lbs./ft.	Wall thickne ☐ Other	ss or gauge No		
Casing height above land TYPE OF SCREEN OF Steel Stai Brass Gal	surface	n. Weight 16.6 TERIAL: erglass XPVC crete tile None	2lbs./ft.	Wall thickne ☐ Other	ss or gauge No		
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal SCREEN OR PERFOR	surface	n. Weight 16.6 ATERIAL: orglass ☑ PVC crete tile ☐ None ARE:	2 lbs./ft.	Wall thickne ☐ Other)	ss or gauge No		
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal SCREEN OR PERFOR Continuous Slot	surface	n. Weight 16.6 TERIAL: orglass PVC crete tile None ARE: Gauze Wrapped T	2 lbs./ft. used (open hole 'orch Cut □ D	Wall thickne ☐ Other) rilled Holes ☐	ss or gauge No (Specify)		
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal SCREEN OR PERFOR Continuous Slot Louvered Shutter	surface	n. Weight 16.6 ATERIAL: orglass PVC crete tile None ARE: Gauze Wrapped T Vire Wrapped S	2 lbs./ft. used (open hole orch Cut □ D aw Cut □ N	Wall thickne Other Other	ss or gauge No (Specify)		
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT	surface	n. Weight 16.6 TERIAL: orglass PVC crete tile None ARE: Gauze Wrapped T Wire Wrapped S m 105	2 lbs./ft. used (open hole orch Cut □ D aw Cut □ N 5 ft., From	Wall thickne Other Other Tilled Holes One (Open Hole The control of the cont	ss or gauge No (Specify)	ft. to ft.	
Casing height above land TYPE OF SCREEN OF Steel Stai Brass Gal- SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA	surface	n. Weight 166 ATERIAL: orglass PVC crete tile None ARE: Gauze Wrapped T Wire Wrapped S m 105 ft. to 125 m 125 ft. to 225	used (open hole orch Cut D aw Cut N ft., From	Wall thickne Other Other rilled Holes one (Open Hole ft. to	SS or gauge No	ft. to ft.	
Casing height above land TYPE OF SCREEN OF Steel Stai Brass Gal- SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA-	surface	n. Weight 16.6 ATERIAL: orglass PVC crete tile None ARE: Gauze Wrapped T Wire Wrapped S m 125 ft. to 225 Cement grout B	used (open hole orch Cut D aw Cut N ft., From dentonite D	Wall thickne Other Other one (Open Hole ft. to ther	SS or gauge No	ft. to ft.	
Casing height above land TYPE OF SCREEN OF Steel Stai Brass Gal- SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA	surface	n. Weight 16.6 ATERIAL: orglass PVC crete tile None ARE: Gauze Wrapped T Wire Wrapped S m 125 ft. to 225 Cement grout B	used (open hole orch Cut D aw Cut N ft., From dentonite D	Wall thickne Other Other one (Open Hole ft. to ther	SS or gauge No	ft. to ft.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal- SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA- GROUT MATERIA Grout Intervals: From Nearest source of possib	surface	n. Weight 16.6 TERIAL: reglass PVC crete tile None None NRE: Gauze Wrapped T Wire Wrapped S m 105 ft. to 125. Cement grout B ft., From	used (open hole forch Cut D aw Cut N f., From D t., From D entonite D ft. to	Wall thickne Other Other Other one (Open Hole ft. to ther	Ss or gauge No	ft. to ft ft.	
Casing height above land TYPE OF SCREEN OF Steel Stai Brass Gal- SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines	surface	n. Weight	used (open hole orch Cut D aw Cut N f., From D ch., From D	Wall thickne Other Other Other One (Open Hole ft. to ther	Ss or gauge No	ft. to ft	
Casing height above land TYPE OF SCREEN OF Steel Stai Brass Gal- SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Li	surface	n. Weight	used (open hole orch Cut D aw Cut N f., From D ch., From D	Wall thickne Other Other Other one (Open Hole ft. to ther	Ss or gauge No	ft. to ft ft.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal- SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Li Other (Specify)	surface	n. Weight A. A	used (open hole orch Cut D aw Cut N ft., From D centonite D agoon D agoon	Wall thickne Other Other Tilled Holes One (Open Hole The to Other The to Other The to Other The to Other Other The to Other Other The storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. dcide Storage loned Water Well ell/Gas Well	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gald SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Li Other (Specify) Direction from well?	surface	n. Weight	used (open hole orch Cut	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OF Steel Stai Brass Gald SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Li Other (Specify) Direction from well? 10 FROM TO	surface	n. Weight	used (open hole orch Cut D aw Cut N ft., From D centonite D agoon D agoon	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. dcide Storage loned Water Well ell/Gas Well	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal-SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Line Other (Specify)	surface	n. Weight	2 lbs./ft. used (open hole forch Cut D aw Cut N f., From D centonite O ft. to D agoon D well? 99	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Galver SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Li Other (Specify) Direction from well? 10 FROM TO 25 25	surface	n. Weight	2 lbs./ft. used (open hole forch Cut D aw Cut N f., From D centonite O ft. to D agoon D well? 99	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gals SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PARENTAL Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Lines Other (Specify)	surface	n. Weight	2 lbs./ft. used (open hole forch Cut D aw Cut N f., From D entonite O ft. to D agoon D FROM	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OF SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA GROUT INTERIA GROUT INTERIA GROUT MATERIA GROUT INTERIA SEWER LINES Watertight Sewer Lines Watertight Sewer Lines Of Other (Specify)	surface	n. Weight	2 lbs./ft. used (open hole forch Cut D aw Cut N f., From D entonite O ft. to D agoon D FROM	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gald SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PART GROUT MATERIA Grout Intervals: From	surface	n. Weight	2 lbs./ft. used (open hole forch Cut D aw Cut N f., From D entonite O ft. to D agoon D FROM	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 25 25 50 60 75 75 75 75 75 75 75 75 75 7	surface	n. Weight	used (open hole forch Cut D aw Cut N f., From ft., From gentonite O agoon D agoon M FROM	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gald SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 25 25 50 60 60 75 75 75 75 75 75 75 75 75 7	surface	n. Weight	used (open hole forch Cut D aw Cut N f., From ft., From gentonite O agoon D agoon M FROM	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gal SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 25 25 50 60 75 75 75 75 75 75 75 75 75 7	surface	n. Weight	used (open hole forch Cut D aw Cut N f., From ft., From gentonite O agoon D agoon M FROM	Wall thickne Other Other Other One (Open Hole ft. to ft. to Other Livestock Pens Fuel Storage Fertilizer Storage	Other (Specify)	ft. to ft. ft. to ft. ft. to ft. ft. to ft. ft. ft. dicide Storage loned Water Well ell/Gas Well tt.	
Casing height above land TYPE OF SCREEN OF SCR	surface	n. Weight	used (open hole forch Cut D aw Cut N ft., From ft., From centonite O agoon D agoon N FROM Notes:	Wall thickne Other Other One (Open Hole fi. to	Ss or gauge No	ft. to ft. ft. to ft. ft. to ft. ft. decide Storage loned Water Well ell/Gas Well t. or PLUGGING INTERVALS	
Casing height above land TYPE OF SCREEN OF SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 25 25 50 60 60 705 705 705 705 705	surface	n. Weight	used (open hole forch Cut D aw Cut N f., From ft., From gentonite O agoon D well? 999 Notes:	Wall thickne Other Other Other Trilled Holes One (Open Hole The to the	Ss or gauge No	ft. to ft. ft. to ft. ft. to ft. cicle Storage loned Water Well ell/Gas Well t. r PLUGGING INTERVALS constructed, or plugged by knowledge and belief.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gals SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Lines Watertight Sewer Lines Other (Specify)	surface	n. Weight	used (open hole forch Cut D aw Cut N ft., From D entonite O agoon D agoon N FROM Notes:	Wall thickne Other Other Other Trilled Holes One (Open Hole The to	Ss or gauge No	ft. to ft. ft. to ft. ft. to ft. cicle Storage loned Water Well ell/Gas Well t. r PLUGGING INTERVALS constructed, or plugged by knowledge and belief.	
Casing height above land TYPE OF SCREEN OI Steel Stai Brass Gals SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PA 9 GROUT MATERIA Grout Intervals: From Nearest source of possib Septic Tank Sewer Lines Watertight Sewer Li Other (Specify) Direction from well? 10 FROM TO 25 25 50 30 40 40 25 11 CONTRACTOR'S under my jurisdiction a Kansas Water Well Counder the business name	surface	n. Weight	used (open hole forch Cut D aw Cut N f., From ft., From gentonite O agoon D well? 999 Notes:	Wall thickne Other Other Other One (Open Hole fi. to ft. to Ther Itivestock Pens Fuel Storage Fertilizer Storage TO LI TO LI To Livestock was component and was component and was component and was component and was component.	Ss or gauge No	ft. to	

KSA 82a-1212

Visit us at http://www.kdheks.gov/waterwell/index.html

Revised 9/10/2012