

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Kiowa	1/4 NC 1/4 W 1/2 1/4	5	T 27 S	R 19 E (W)

Distance and direction from nearest town or city street address of well if located within city?
 Approximately 6 miles south and 8 3/4 miles west of Centerview

2 WATER WELL OWNER: Edward R. Miller Trust
 RR#, St. Address, Box #: Route 1 - Box 122 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Mullinville, KS 67109 Application Number: 15,105

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 167 ft. ELEVATION: unknown
--	--

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 52.85 ft. below land surface measured on mo/day/yr 4-13-01

Pump test data: Well water was not checked ft. after hours pumping gpm

Est. Yield unknown gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 24 in. to 168 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
9 Dewatering	10 Monitoring well	12 Other (specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded	<input checked="" type="checkbox"/>
		7 Fiberglass		Threaded	

Blank casing diameter 16 in. to 126 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 36.87 lbs./ft. Wall thickness or gauge No .219

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) Bridge Slot	

SCREEN-PERFORATED INTERVALS: From 126 ft. to 166 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 60 ft. to 168 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Road Sand

Grout Intervals: From 0 ft. to 24 ft., From ft. to ft., From 24 ft. to 60 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None known

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	SCREENING INTERVALS
0	4	Topsoil	143	165	Sand and gravel, fine, medium
4	18	Clay, gray	165	168	Clay, white
18	25	Sand and gravel, fine, medium			
25	54	Sand and gravel, fine, medium, coarse			
54	56	Clay, orange			
56	68	Sand and gravel, fine, medium, coarse			
68	75	Clay, brown with sand and gravel			
75	86	Sand and gravel, fine, medium, coarse			
86	95	Clay, tan			
95	102	Sand and gravel, fine, medium, coarse			
102	112	Clay, light brown			
112	121	Clay, white			
121	140	Sand and gravel, fine, medium			
140	143	Clay, brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-12-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 4-17-01 under the business name of Clarke Well & Equipment, Inc. by (signature) *Clarke Well & Equipment, Inc.*