USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Controctors) Topeka, Kansas 66620

| | County | Fraction | Section number | | Township number | Range number |] |
|---|--------------|------------------|----------------|------------|---|---|----------------------------|
| 1. Location of well: | Kiowa | 1/4 c 1/4 se 1/4 | | 12 | т 27 s | R 19 E/W | |
| 2. Distance and direction from nearest town or city: 1-W 7-N 12-W north side from Greensburg, KSB.R. or street: Street address of well focation if in city: City, state, zip code: | | | | | Hutchinson National Bank Box 1488 Hutchinson, Kansas 67501 | | |
| 4. Locate with "X" in section below: N | | | | | 6. Bore hole dia. <u>29</u> in Well depth <u>185</u> ft. | | |
| | | | | | 7 Cable tool X Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other | | |
| | | | | | 9. Casing: Material Stee Height: Above or MAN Threaded Welded Surface 24 in. RMP PVC Weight lbs./ft. Dia. 16n. to 165ft. depth Wall Thickness: inches or | | |
| 5. Type and color of material | | | | То | Diain. to ft. dep 10. Screen: Manufacturer's n | h gage No. | - |
| sandy top soil | | | | 2 | Doerrs Type_steelDig | | |
| fin e sand | | | 2 | 12 | Slot/2642e 3/16 Length & O Set between 105 ft. and 185 ft. ft. and ft. Gravel pack? X Size range of material 3/4 3/8 | | |
| clay | | | 12 | 17 | | | |
| sand & gravel | | | 17 | 72 | 11. Static water level: mo./day/yr. 12. 12. 12. 12. 12. 12. 12. 12. 12. 12. | | |
| brown clay | | | 72 | 86 | 12. Pumping level below land | surfaces: ars. pumping 600 g.p.m. | |
| sand & gravel | | | 86 | 100 | ft. after hrs. pumping g.p.m. Estimated maximum yield 1400+ g.p.m. | | |
| brown & white clay | | | | 107 | 13. Water sample submitted: mo./day/yr. X Yes No Date | | |
| sand & gravel | | | | 112 | 14. Well head completion: | | |
| brown clay w/gravel mixed | | | | 114 | Pitless adapter 15. Well grouted? X | Inches above grode | <u>ا</u> ا |
| sand & gravel | | | | 119 | With: X Neat cement Bentonite Cancrete Depth: From ft. to ft. | | |
| brown clay | | | + | 137 | 16. Nearest source of possible contamination: ft. 34mi Direction South Type Oliwell | | - |
| sand & gravel w/clay mixed | | | 137 | 147 | Well disinfected upon comple | | 1 |
| clay | | | 147 | 150 | Manufacturer's name | | ~ 4 |
| sand & gravel | | | + | 168 | | | 8 |
| clay | | | 1 | 177 | | | ١, |
| sand & gravel yellow clay & light (Use a second sheet if needed) 18 Elevation 19 Remorks. gray clay | | | 177 188 | 188 193 | Jet Centrifugal | Reciprocating Other | Sec |
| Topography: Hill Slope X Upland | 19. Remarks: | α. , | | | Signed anduke | y jurisdiction and this report ledge and belief. | 3/10 1/1 1/1 1/1 St 04 1/1 |