

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

Table with 5 columns: LOCATION OF WATER WELL, Fraction, Section Number, Township Number, Range Number. Includes County: Kiowa, Fraction: N/4 NC N/4 SE 1/4, Section Number: 28, Township Number: T 27 S, Range Number: R 19 NW.

Distance and direction from nearest town or city street address of well if located within city? 5 1/2 West, 3 1/4 North of Greensburg

Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: Spring Creek RR#, St. Address, Box # : 3945 Windmill Run Dr City, State, ZIP Code : Wamego, Ks. 66547

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Includes a 4x4 grid diagram with 'X' in the SE quadrant. 4 DEPTH OF COMPLETED WELL: 170 ft. WELL'S STATIC WATER LEVEL: 82 ft. below land surface. Pump test data: 101 ft. after 3 1/2 hours pumping, 1000 gpm. Est. Yield: 116 gpm. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Domestic (lawn & garden), 10 Monitoring well.

5 TYPE OF CASING USED: 5 Wrought Iron, 8 Concrete tile, CASING JOINTS: Glued, Clamped, Welded, Threaded. 1 Steel, 3 RMP (SR), 6 Asbestos-Cement, 9 Other (specify below). 2 PVC, 4 ABS, 7 Fiberglass. Blank casing diameter: 16 in. to 100 ft., Diameter. Casing height above land surface: 24 in., Weight Sch. 40 lbs./ft. Wall thickness or guage No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless Steel, 5 Fiberglass, 7 PVC, 9 ABS, 11 Other (Specify). 2 Brass, 4 Galvanized Steel, 6 Concrete tile, 8 RM (SR), 10 Asbestos-Cement, 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 7 Torch cut, 9 Drilled holes, 11 None (open hole). 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, 8 Saw cut, 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 170 ft. to 100 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 170 ft. to 20 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other hole plug. Grout Intervals: From ft. to ft., From ft. to ft., From 20 ft. to 0 ft. What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 13 Insecticide storage, 16 Other (specify below) None. 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 14 Abandoned water well. 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 15 Oil well/gas well. Direction from well? How many feet?

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: 0-4 Top soil, 4-9 Brown clay, 9-19 Reddish brown sandy clay with bits of fine sand, 19-48 Clay & small gravel mixed, 48-89 Small gravel-tight, 89-92 Light tan clay, 92-112 Small to med gravel, 112-115 Tan clay/caliche/few lg rocks, 115-133 Tan clay/ small gravel & mixed.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-16-10 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 5-5-10 under the business name of Rosencrantz- Bemis by (signature) John Alab

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.