WATER WELL RECORD Form WWC-5 KSA 82a-1212

COUNTY: KIOWA	NW 1	on 1/4 SB 1/4 NW 1/4	Section Number	T 27	Ş	R 19 W	,
Distance and direction from 2 MILES NORTH, 5 MILES WEST	nearest to	own or city street address o BURG	f well if located	d within city?			
WATER WELL OWNER: RR#, St. Address, Box # : I City, State, ZIP code : I	PO ROY 7500		Board of Agricu Application Num		n of Water R	Resources	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL Depth(s) Groundwater Enc	152ELEVATION: ountered 1.	0 . 0 ft.	2. 0 ft	z. 3.) ft
		WELL'S STATIC WATER LEVEL Pump testdata:	86 ft. below l Well water was				2/05) gp
L NW NB		· · ·	Well water was) gp
. W -	B	Bore Hole Diameter	8.75 in. to 16	60 ft., and	in. to	0 ft.	
.		WELL WATER TO BE USED AS:				1	
<u> </u>		Was a chemical/bacteriolog If yes, mo/day/yr sample w	ical sample submi as submitted	itted to departm	nent? No ; Water wel	ll disinfected	Ye
Blank casing diameter 59 Casing height above land sur TYPE OF SCREEN OR PERFORATION	5 in. t rface 12 ON MATERIAL	L: P♥C	GLUKD to Oft., D /ft. Wall thickn	Dia in. to ness or gauge No	0 ft. 0. 26		
Blank casing diameter 5 Casing height above land sur	5 in. t rface 12 ON MATERIAL NGS ARE:	to 132 ft., Dia in. 2 in., weight 0 lbs 4: PVC SAW CUT From 132 ft. to 152 ft. From 0 ft. to 0 ft.	to 0 ft., D /ft. Wall thickn , From 0 ft. , From 0 ft.	to 0 ft.	0 ft.		
TYPE OF SCREEN OR PERFORATION OPENING SCREEN OR PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE GROUT Intervals: From	5 in. trface 12 ON MATERIAL NGS ARE: ::	to 132 ft., Dia in. 2 in., weight 0 lbs 4: PVC SAW CUT From 132 ft. to 152 ft. From 0 ft. to 0 ft. From 25 ft. to 152 ft. From 0 ft. to 0 ft.	to 0 ft., D /ft. Wall thickn , From 0 ft.	to 0 ft. to 0 ft. to 0 ft. to 0 ft.	0 ft.	ow many feet?	300
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATIO SCREEN OR PERFORATION OPENIN SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 2 What is the nearest source of Direction from well? EAST FROM TO 50 SILT AND 50 58 GRAVEL 58 62 TAN CLAY	5 in. trace 12 ON MATERIAL NGS ARE: : : : 2 ft. to of possible LIT D SAND	to 132 ft., Dia in. 2 in., weight 0 lbs 4: PVC SAW CUT From 132 ft. to 152 ft. From 0 ft. to 0 ft. From 25 ft. to 152 ft. From 0 ft. to 0 ft. 25 ft., From 0 ft. to	to 0 ft., D /ft. Wall thickn , From 0 ft.	to 0 ft. to 0 ft. to 0 ft. to 0 ft.	0 ft.	·	300
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATIO SCREEN OR PERFORATION OPENIN SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From What is the nearest source of Direction from well? EAST FROM TO 0 50 SILT ANI 50 58 GRAVEL 58 62 TAN CLAY	5 in. t rface 12 ON MATERIAL NGS ARE: : : : : D SAND Y D GRAVEL LAY	to 132 ft., Dia in. 2 in., weight 0 lbs 2: PVC SAW CUT From 132 ft. to 152 ft. From 0 ft. to 0 ft. From 25 ft. to 152 ft. From 0 ft. to 0 ft. From 0 ft. to 0 ft. Contamination: OIL/GAS WEL	to 0 ft., D /ft. Wall thickn , From 0 ft.	to 0 ft. to 0 ft. to 0 ft. to 0 ft.	O ft.	·	300
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATION SCREEN OR PERFORATION OPENIN SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From What is the nearest source of Direction from well? EAST FROM TO 0 50 SILT ANI 50 58 GRAVEL 58 62 TAN CLAY 62 108 SAND ANI 108 114 WHITE CI 114 124 SAND ANI 124 133 BROWN CI	5 in. t rface 12 ON MATERIAL NGS ARE: : : : : D SAND Y D GRAVEL LAY D GRAVEL LAY LAY	to 132 ft., Dia in. 2 in., weight 0 lbs 2: PVC SAW CUT From 132 ft. to 152 ft. From 0 ft. to 0 ft. From 25 ft. to 152 ft. From 0 ft. to 0 ft. From 0 ft. to 0 ft. Contamination: OIL/GAS WEL	to 0 ft., D /ft. Wall thickn , From 0 ft.	to 0 ft. to 0 ft. to 0 ft. to 0 ft.	O ft.	·	300
Blank casing diameter Casing height above land sur TYPE OF SCREEN OR PERFORATIO SCREEN OR PERFORATION OPENIN SCREEN OR PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From What is the nearest source of Direction from well? EAST FROM TO 0 50 SILT ANI 50 58 GRAVEL 58 62 TAN CLAY 62 108 SAND ANI 108 114 WHITE CI 114 124 SAND ANI 124 133 BROWN CI	5 in. t rface 12 ON MATERIAL NGS ARE: : : : : D SAND Y D GRAVEL LAY D GRAVEL LAY D GRAVEL LAY D GRAVEL LAY	to 132 ft., Dia in. 2 in., weight 0 lbs 2: PVC SAW CUT From 132 ft. to 152 ft. From 0 ft. to 0 ft. From 25 ft. to 152 ft. From 0 ft. to 0 ft. From 0 ft. to 0 ft. Contamination: OIL/GAS WEL	to 0 ft., D /ft. Wall thickn , From 0 ft.	to 0 ft. to 0 ft. to 0 ft. to 0 ft.	O ft.	·	300