


1 LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NW 1/4 NE 1/4	Section Number 24	Township Number T 27 S	Range Number R 2W E/W																																																			
Distance and direction from nearest town or city street address of well if located within city? 522 Bay Country Wichita, Kansas																																																							
2 WATER WELL OWNER: YATES, Ron RR#, ST. ADDRESS, BOX #: 522 Bay Country CITY, STATE, ZIP CODE: Wichita, Kansas																																																							
Board of Agriculture, Division of Water Resource Application Number:																																																							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 63 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 05/31/1996 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 63 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No																																																						
5 TYPE OF CASING USED: <table style="width:100%;"> <tr> <td>1 Steel</td> <td>3 RMP (SR)</td> <td>5 Wrought iron</td> <td>8 Concrete tile</td> <td>CASING JOINTS:</td> <td>Glued ☒</td> <td>Clamped</td> </tr> <tr> <td>2 PVC</td> <td>4 ABS</td> <td>6 Asbestos-Cement</td> <td>9 Other (Specify below)</td> <td></td> <td>Welded</td> <td></td> </tr> <tr> <td></td> <td></td> <td>7 Fiberglass</td> <td>SDR-26</td> <td></td> <td>Threaded</td> <td></td> </tr> </table> Blank casing Diameter 5 in. to 43 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: <table style="width:100%;"> <tr> <td>1 Steel</td> <td>3 Stainless Steel</td> <td>5 Fiberglass</td> <td>7 PVC</td> <td>10 Asbestos-cement</td> </tr> <tr> <td>2 Brass</td> <td>4 Galvanized steel</td> <td>6 Concrete tile</td> <td>8 RMP (SR)</td> <td>11 other (specify)</td> </tr> <tr> <td></td> <td></td> <td></td> <td>9 ABS</td> <td>12 None used (open hole)</td> </tr> </table> SCREEN OR PERFORATION OPENING ARE: <table style="width:100%;"> <tr> <td>1 Continuous slot</td> <td>3 Mill slot</td> <td>5 Gauzed wrapped</td> <td>8 Saw cut</td> <td>11 None (open hole)</td> </tr> <tr> <td>2 Louvered shutter</td> <td>4 Key punched</td> <td>6 Wire wrapped</td> <td>9 Drilled holes</td> <td></td> </tr> <tr> <td></td> <td></td> <td>7 Torch cut</td> <td>10 Other (specify)</td> <td></td> </tr> </table> SCREEN-PERFORATION INTERVALS: from 43 ft. to 63 ft., From ft. to ft. from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from 24 ft. to 63 ft., From ft. to ft. from ft. to ft., From ft. to ft.					1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS:	Glued ☒	Clamped	2 PVC	4 ABS	6 Asbestos-Cement	9 Other (Specify below)		Welded				7 Fiberglass	SDR-26		Threaded		1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC	10 Asbestos-cement	2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 other (specify)				9 ABS	12 None used (open hole)	1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes				7 Torch cut	10 Other (specify)	
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS:	Glued ☒	Clamped																																																	
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (Specify below)		Welded																																																		
		7 Fiberglass	SDR-26		Threaded																																																		
1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC	10 Asbestos-cement																																																			
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 other (specify)																																																			
			9 ABS	12 None used (open hole)																																																			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)																																																			
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes																																																				
		7 Torch cut	10 Other (specify)																																																				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: <table style="width:100%;"> <tr> <td>1 Septic tank</td> <td>4 Lateral lines</td> <td>7 Pit privy</td> <td>10 Livestock pens</td> <td>14 Abandon water well</td> </tr> <tr> <td>2 Sewer lines</td> <td>5 Cess pool</td> <td>8 Sewage lagoon</td> <td>11 Fuel storage</td> <td>15 Oil well/Gas well</td> </tr> <tr> <td>3 Watertight sewer lines</td> <td>6 Seepage pit</td> <td>9 Feedyard</td> <td>12 Fertilizer storage</td> <td>16 Other (specify below)</td> </tr> </table> 13 Insecticide storage None Apparent Direction from well? How many feet?					1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)																																				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandon water well																																																			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well																																																			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)																																																			
FROM 0 2 20 57	TO 2 20 57 63	LITHOLOGIC LOG topsoil clay medium to coarse sand clay			FROM 	TO 	PLUGGING INTERVALS 																																																
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/31/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 05/31/96 Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick																																																							