

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sedgwick		SW 1/4 NE 1/4 SE 1/4		13		T 27 S		R 2W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
Hickory St. and Cedar Park (Deer Glen At Buckhead) Wichita, Kansas									
WATER WELL OWNER: KELSEY, Paul									
RR#, ST. ADDRESS, BOX #: 716 N. 119th W. Unit #112									
CITY, STATE, ZIP CODE: Wichita, Kansas 67235									
Board of Agriculture, Division of Water Resource Application Number:									
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 140 ft. ELEVATION:							
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.							
		WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 06/25/1996							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm : Well water was ft. after hours pumping gpm							
Bore Hole Diameter 12 in. to 140 ft. and in. to ft.		WELL WATER TO BE USED AS:							
1 Domestic		3 Feedlot		6 Oil field water supply		8 Air conditioning		11 Injection well	
2 Irrigation		4 Industrial		7 Lawn and garden only		9 Dewatering		12 Other (Specify below)	
WAS A chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes ☒ No ☐									
5 TYPE OF CASING USED:									
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued ☐ Clamped ☒	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (Specify below)		Welded	
				7 Fiberglass		SDR-26		Threaded	
Blank casing Diameter 5 in. to 100 ft., Dia		in. to 100 ft., Dia		in. to 100 ft., Dia		in. to 100 ft., Dia		in. to 100 ft., Dia	
Casing height above land surface 12 in., weight 2.35 lbs. / ft.		in. to 100 ft., weight 2.35 lbs. / ft.		in. to 100 ft., weight 2.35 lbs. / ft.		in. to 100 ft., weight 2.35 lbs. / ft.		in. to 100 ft., weight 2.35 lbs. / ft.	
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel		3 Stainless Steel		5 Fiberglass		8 RMP (SR)		11 other (specify)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENING ARE:									
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes			
				7 Torch cut		10 Other (specify)			
SCREEN-PERFORATION INTERVALS:									
from 100 ft. to 140 ft., From		ft. to 140 ft., From		ft. to 140 ft., From		ft. to 140 ft., From		ft. to 140 ft., From	
GRAVEL PACK INTERVALS:		from 24 ft. to 140 ft., From		ft. to 140 ft., From		ft. to 140 ft., From		ft. to 140 ft., From	
6 GROUT MATERIAL:									
1 Neat cement		2 Cement grout		3 Bentonite		4 Other bentonite hole plug			
Grout Intervals: From 4 ft. to 24 ft. From		ft. From		ft. to		ft. From		ft. to	
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandon water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
						13 Insecticide storage		None Apparent	
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	4	topsoil							
4	18	clay							
18	30	fine sand							
30	65	medium coarse sand							
65	75	clay							
75	85	fine sand							
85	95	clay							
95	125	medium sand							
125	130	clay							
130	140	medium sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 06/25/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 06/26/96 Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp									