

LOCATION OF WATER WELL:

FRACTION

Section Number

Township Number

Range Number

Sedgwick

SE 1/4 SE 1/4 SW 1/4

24

T 27 S

R 2W E/W

Distance and direction from nearest town or city street address of well if located within city?

272 S. Forestview Wichita, Kansas

WATER WELL OWNER: LEWIS, Darrel

Board of Agriculture, Division of Water Resource

ARW, ST. ADDRESS, BOX #: 272 S. Forestview

Application Number:

CITY, STATE, ZIP CODE: Wichita, Kansas

LOCATE WELL'S LOCATION WITH "X" IN SECTION BOX:

N

NE

SE

S

SW

W

E

DEPTH OF COMPLETED WELL 76 ft. ELEVATION:

Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 07/15/1996

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 12 in. to 76 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

TYPE OF CASING USED:

5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded

2 PVC 4 ABS 7 Fiberglass SDR-26 Threaded

Blank casing Diameter 5 in. to 56 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No. .214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENING ARE:

5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 9 Drilled holes

2 Covered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATION INTERVALS:

from 56 ft. to 76 ft., From ft. to ft.

GRAVEL PACK INTERVALS:

from 24 ft. to 76 ft., From ft. to ft.

ROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Cement Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

10 Livestock pens 14 Abandon water well

Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

1 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

1 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? East How many feet? 25

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

2 topsoil

15 clay

50 fine to medium sand

72 medium to coarse sand

76 clay

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/15/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 07/16/96 under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp