

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 SE 1/4 NW 1/4 SW 1/4	Section Number 24 25	Township Number T 27 S	Range Number R 2W E/W	
Distance and direction from nearest town or city street address of well if located within city: 490 Limuel Wichita, Kansas					
WATER WELL OWNER: JACKSON, Brian		Board of Agriculture, Division of Water Resource			
RR#, ST. ADDRESS, BOX #: 490 Limuel		Application Number:			
CITY, STATE, ZIP CODE: Wichita, Kansas					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION:				
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.				
	WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON 08/31/1996				
	Pump test data: Well water was ft. after hours pumping gpm				
	Est. Yield gpm: Well water was ft. after hours pumping gpm				
Bore Hole Diameter 12 in. to 60 ft. and in. to ft.					
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No					
5 TYPE OF CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (Specify below) Welded			
		7 Fiberglass SDR-26 Threaded			
Blank casing Diameter 5 in. to 25 ft., Dia in. to ft.		Weight 2.35 lbs. / ft. Wall thickness or gauge No. .214			
Casing height above land surface 12 in.,					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel		5 Fiberglass 8 RMP (SR) 11 other (specify)			
2 Brass 4 Galvanized steel		6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:					
1 Continuous slot 3 Mill slot		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
2 Louvered shutter 4 Key punched		6 Wire wrapped 9 Drilled holes			
		7 Torch cut 10 Other (specify)			
SCREEN-PERFORATION INTERVALS: from 25 ft. to 60 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: from 24 ft. to 60 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines		7 Pit privy 10 Livestock pens 14 Abandon water well			
2 Sewer lines 5 Cess pool		11 Fuel storage 15 Oil well/Gas well			
3 Watertight sewer lines 6 Seepage pit		12 Fertilizer storage 16 Other (specify below)			
		13 Insecticide storage			
Direction from well? South How many feet? 25					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	15	clay			
15	35	medium tmo coarse sand			
35	49	clay			
49	60	medium sand			
60	65	shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/31/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/03/96 Under the business name of Harp Well & Pump Service, Inc by (signature) <i>Todd S. Harp</i>					