

1 LOCATION OF WATER WELL: County: Sedgwick NE 1/4 SW 1/4 NW 1/4 25 Township Number: T 27 S Range Number: R 2 EW

Distance and direction from nearest town or city street address of well if located within city? 409 S. Limuel - by pool

2 WATER WELL OWNER: Auburn Hills Homeowners Assn. RR#, St. Address, Box #: 8815 W. 13th City, State, ZIP Code: Wichita, KS 67212

Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with an 'X' in the NW section of the top-left 4-section block]

4 DEPTH OF COMPLETED WELL: 47 ft. ELEVATION: 8127.197 ft.

Depth(s) Groundwater Encountered: 19 ft. WELL'S STATIC WATER LEVEL: 19 ft. below land surface measured on mo/day/yr 8/27/97

Pump test data: Well water was 20 gpm. Est. Yield: 20 gpm. Well water was 11 in. Bore Hole Diameter: 11 in. to 47 ft. and 47 in. to 47 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded

Blank casing diameter: 5 in. to 35 ft. Dia. 2.40 in. to 160 PSI Casing height above land surface: 12 in. weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut

SCREEN-PERFORATED INTERVALS: From 35 ft. to 47 ft. From 19 ft. to 47 ft.

GRAVEL PACK INTERVALS: From 19 ft. to 47 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 19 ft. From 19 ft. to 25 ft. From 25 ft. to 47 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? north How many feet? 25

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 25 clay

25 35 coarse gravel

35 40 clay

40 47 fine sugar sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/27/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 218 This Water Well Record was completed on (mo/day/yr) 8/27/97 under the business name of Winger Drilling Inc. by signature Michelle Becker

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.