

LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number		
Sedgwick		SW	1/4	SE	1/4	NE	1/4	13	T 27 S	R 2W E/W

Distance and direction from nearest town or city street address of well if located within city?

1002 Cedar Park

Wichita, Kansas

WATER WELL OWNER: COTNER, Ron
RR#, ST. ADDRESS, BOX #: 1002 Cedar Park
CITY, STATE, ZIP CODE: Wichita, Kansas

Board of Agriculture, Division of Water Resource

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4	DEPTH OF COMPLETED WELL	73	ft.	ELEVATION:	
	Depth(s) groundwater Encountered	1	ft.	2	ft.
	WELL'S STATIC WATER LEVEL	29	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr	12/17/1998

Pump test data:		Well water was		ft.	after	hours	pumping	gpm
Est. Yield	gpm:	Well water was		ft.	after	hours	pumping	gpm
Bore Hole Diameter	12	in.	to 73	ft.	and	in.	to	ft.
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well		
1 Domestic	3 Feedlot	6 Oil field water supply		9 Dewatering		12 Other (Specify below)		
2 Irrigation	4 Industrial	7 Lawn and garden only		10 Monitoring well				

Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted _____

Water Well Disinfected? Yes ☒ No ☐

5	TYPE OF CASING USED:
---	----------------------

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)	Welded
2 PVC	4 ABS	7 Fiberglass	SDR - 26	Threaded
Blank casing Diameter	5 in. to 53	ft., Dia	in. to	ft., Dia
Casing height above land surface	12 in.,	weight 2.35	lbs. / ft.	Wall thickness or gauge No. .214
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENING ARE:

1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)

SCREEN-PERFORATION INTERVALS:	from 53	ft. to 73	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:	from 24	ft. to 73	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.

6	GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	bentonite hole plug
---	-----------------	---------------	----------------	-------------	---------	---------------------

Grout Intervals:		From	ft. to	ft.	From	ft. to	ft.	From	ft. to	ft.
		4		24						

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	

Direction from well? East

How many feet? 40

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/17/1998 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 12/21/98 Under the business name of Harp Well & Pump Service, Inc. by (signature)

Todd S. Harp