

1 LOCATION OF WATER WELL:		FRACTION			Section Number		Township Number		Range Number	
Sedgwick		NW 1/4 SE 1/4 SE 1/4			24		T 27 S		R 2W E/W	

Distance and direction from nearest town or city street address of well if located within city?

12210 W. Texas Wichita, Kansas

WATER WELL OWNER: STEWART, Norma

RR#, ST. ADDRESS, BOX #: 12210 W. Texas


CITY, STATE, ZIP CODE : **Wichita, Kansas**

Board of Agriculture, Division of Water Resource

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4	DEPTH OF COMPLETED WELL	80	ft.	ELEVATION:	
	Depth(s) groundwater Encountered	1	ft.	2	ft.
	WELL'S STATIC WATER LEVEL	25	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr	02/24/1999



Pump test data:		Well water was		ft.	after	hours pumping	gpm
Est. Yield	gpm:	Well water was		ft.	after	hours pumping	gpm
Bore Hole Diameter	12	in.	to 80	ft.	and	in. to	ft.
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well	
1 Domestic	3 Feedlot	6 Oil field water supply		9 Dewatering		12 Other (Specify below)	
2 Irrigation	4 Industrial	7 Lawn and garden only		10 Monitoring well			

Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ ; If yes, mo/day/yr sample was submitted _____

Water Well Disinfected? Yes ☒ No ☒

5	TYPE OF CASING USED:
---	----------------------

1 Steel	3 RMP (SR)
2 PVC	4 ABS

5 Wrought iron
6 Asbestos-Cement
7 Fiberglass

8 Concrete tile
9 Other (Specify below)

CASING JOINTS: **Glued** **X** **Clamped**
 Welded
 Threaded

Blank casing Diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface	12	in.	weight	2.35	lbs. / ft.	Wall thickness or gauge No.	.214
----------------------------------	----	-----	--------	------	------------	-----------------------------	------

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel
2 Brass 4 Galvanized steel

5 Fiberglass
6 Concrete tile

7 PVC
8 RMP (SR)
9 ABS

10 Asbestos-cement
11 other (specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENING ARE:

1 Continous slot	3 Mill slot
2 Louvered shutter	4 Key punched

5 Gauzed wrapped
6 Wire wrapped
7 Torch cut

8 Saw cut
9 Drilled holes
10 Other (specify)
11 None (open hole)

SCREEN-PERFORATION INTERVALS:	from 60	ft. to 80	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:	from 24	ft. to 80	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.

6	GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	bentonite hole plug
---	-----------------	---------------	----------------	-------------	---------	---------------------

Grout Intervals: From 4		ft. to 24		ft. From		ft. to		ft. From		ft. to		ft.	
-------------------------	--	-----------	--	----------	--	--------	--	----------	--	--------	--	-----	--

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)

Direction from well? North How many feet? 150

[illegible]

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/24/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 02/26/99 Under the business name of Harp Well & Pump Service, Inc. by (signature)

Todd S. Harp