

1 LOCATION OF WATER WELL: County: Sedgwick NW 1/4 NW 1/4 SE 1/4 Section Number 15 Township Number T 27 S Range Number R 2 E/W

Distance and direction from nearest town or city street address of well if located within city? 15835 Hickory

2 WATER WELL OWNER: Ron Bouska RR#, St. Address, Box #: 8201 E. Harry City, State, ZIP Code: Wichita, KS 67207 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SE section of the NW quarter]

4 DEPTH OF COMPLETED WELL: 81 ft. ELEVATION: 4-20-00

WELL'S STATIC WATER LEVEL: 18 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 11 in. to 81 ft. after 18 hours pumping gpm

Est. Yield 20 gpm: Well water was 11 in. to 81 ft. after 18 hours pumping gpm

Bore Hole Diameter: 11 in. to 81 ft. and 11 in. to 81 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded

Blank casing diameter 5 in. to 12 in. Dia 2.40 in. Dia 160psi

Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160psi

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) 9 ABS

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 18 ft. to 81 ft. From 18 ft. to 81 ft.

GRAVEL PACK INTERVALS: From 18 ft. to 81 ft. From 18 ft. to 81 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 18 ft. From 18 ft. to 81 ft. From 18 ft. to 81 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? Southwest How many feet? 110

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 16 Clay

16 20 med. sand

20 81 shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-20-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 38 This Water Well Record was completed on (mo/day/yr) 4-20-00 under the business name of Weninger Drilling Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.