

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW 1/4 NE 1/4 NW 1/4		Section Number 13		Township Number T 27 S		Range Number R 2W E/W	
Distance and direction from nearest town or city street address of well if located within city? 1309 N. Hickory Creek Ct. Wichita, Kansas									
WATER WELL OWNER: CRAMER, Rebecca RR#, ST. ADDRESS, BOX #: 1309 N. Hickory Creek Ct. CITY, STATE, ZIP CODE: Wichita, Kansas					Board of Agriculture, Division of Water Resource Application Number:				
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 			4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:						
			Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.						
			WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 7-15-2002						
			Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 80 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED:									
1 Steel 3 RMP (SR)			5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped				
2 PVC 4 ABS			6 Asbestos-Cement 9 Other (Specify below)		Welded				
Blank casing Diameter 5 in. to 60 ft., Dia in. to ft. , Dia in. to ft.			7 Fiberglass SDR-26		Threaded				
Casing height above land surface 12 in., weight 2.35 lbs. / ft.			Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless Steel			5 Fiberglass 8 RMP (SR)		10 Asbestos-cement				
2 Brass 4 Galvanized steel			6 Concrete tile 9 ABS		11 other (specify)				
SCREEN OR PERFORATION OPENING ARE:			5 Gauzed wrapped 8 Saw cut		11 None (open hole)				
1 Continuous slot 3 Mill slot			6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched			7 Torch cut 10 Other (specify)						
SCREEN-PERFORATION INTERVALS: from 60 ft. to 80 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: from 24 ft. to 80 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines			7 Pit privy		10 Livestock pens		14 Abandon water well		
2 Sewer lines 5 Cess pool			8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well		
3 Watertight sewer lines 6 Seepage pit			9 Feedyard		12 Fertilizer storage		16 Other (specify below)		
Direction from well? West					How many feet? 100				
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS						
0	4	topsoil							
4	35	clay							
35	50	medium coarse sand							
50	55	clay							
55	60	fine sand							
60	80	medium sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-15-2002 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 7-17-2002									
Under the business name of Harp Well & Pump Service, Inc by (signature) <i>Todd S. Harp</i>									