

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NE 1/4 Section Number 12 Township Number 27 S Range Number 2 E

County: Sedgwick Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Tina Smith See below

RR#, St. Address, Box #: 2054 Sunridge Ct. Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Wichita, KS 67235 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 3-20-02

Depth(s) Groundwater Encountered: 1 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 30 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield: 20 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 11 in. to 66 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped.

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 5 4 ABS 7 Fiberglass Threaded

Blank casing diameter: 5 in. to 46 ft. Dia. in. to ft. Dia. to ft.

Casing height above land surface: 12 in., weight: 2.40 lbs./ft. Wall thickness or gauge No. 16 gage

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From: 46 ft. to 66 ft. From: ft. to ft.

GRAVEL PACK INTERVALS: From: 30 ft. to 66 ft. From: ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From: 3 ft. to 30 ft. From: ft. to ft. From: ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? West How many feet? 30

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 top soil

2 25 clay

25 40 med sand

40 42 clay

42 66 fine to med sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-20-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 38 This Water Well Record was completed on (mo/day/yr) 3-21-02 under the business name of Nutter Drilling Inc by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.