

1] LOCATION OF WATER WELL		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		NW 1/4 NE 1/4 NW 1/4		27		T 27 S		R 2 E	
Distance and direction from nearest town or city street address of well if located within city? see below									
2] WATER WELL OWNER: MIKE HOBBS									
RR#, St. Address, Box #: 340 S. 162nd W.									
City, State, ZIP Code: Goddard KS. 66110									
Board of Agriculture, Division of Water Resources									
Application Number:									
3] LOCATE WELL'S LOCATION WITH					4] DEPTH OF COMPLETED WELL				
AN "X" IN SECTION BOX:					ft. ELEVATION:				
					Depth(s) Groundwater Encountered 35 ft. 2. ft. 3. ft.				
					WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr				
					Pump test data: Well water was ft. after hours pumping gpm				
					Est. Yield 25 gpm; Well water was ft. after hours pumping gpm				
					Bore Hole Diameter 11 in. to 110 ft. and in. to ft.				
					WELL WATER TO BE USED AS:				
					5 Public water supply 8 Air conditioning 11 Injection well				
					1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
					2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well				
Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes X No									
5] TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped.									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded.									
Blank casing diameter 5 in. to 30 ft. Dia 2.40 in. to ft. Dia in. to ft.									
Casing height above land surface 2 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 14.0									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify) ft.									
SCREEN-PERFORATED INTERVALS: From 30 ft. to 110 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 35 ft. to 110 ft. From ft. to ft.									
6] GROUT MATERIAL:									
1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 3 ft. to 35 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? East How many feet? 80									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 35 clay									
35 110 charcoal shale									
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-7-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 8-8-03 under the business name of Weninger Drilling Inc. by (signature) Thichelecoro									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.									