

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NE 1/4 SE 1/4 NE 1/4		SECTION NUMBER 12	TOWNSHIP NUMBER T 27 S		RANGE NUMBER R 2W E/W	
Distance and direction from nearest town or city street address of well if located within city? 12112 W. Eberly Ct. Wichita, Kansas								
2 WATER WELL OWNER: JONES, Dirk		Board of Agriculture, Division of Water Resource						
RR#, ST. ADDRESS, BOX #: 12112 W. Eberly Ct.		Application Number:						
CITY, STATE: Wichita, Kansas		ZIP CODE:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 130 ft. ELEVATION:						
1 Mile		Depth of groundwater Encountered: ft.						
		WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 9/16/03						
		Pump test data: Well water was ft. after hours of pumping @ gpm						
		Est. Yield: gpm Well water was ft. after hours of pumping @ gpm						
		Bore Hole Diameter 12 in. to 130 ft. and in. to ft.						
		WELL WATER TO BE USED AS:						
		1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well						
		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)						
		Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted						
		Was Water Well Disinfected? YES NO						
5 TYPE OF CASING USED:		CASING JOINTS: Glued Threaded						
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below)		Welded Clamped						
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26								
Blank casing diameter 5 in. to 110 ft., Dia. in. to ft., Dia. in. to ft.								
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)								
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)								
SCREEN - PERFORATION INTERVAL		From 110 ft. to 130 ft., From ft. to ft.						
GRAVEL PACK INTERVALS:		From 24 ft. to 130 ft., From ft. to ft.						
6 GROUT MATERIALS:		Other bentonite hole plug						
1. Neat cement 2. Cement Grout 3. Bentonite								
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well?		How many feet?						
From To LITHOLOGIC LOG		From To LITHOLOGIC LOG						
0	4	topsoil						
4	20	clay						
20	35	medium sand						
35	40	clay						
40	60	medium sand						
60	95	clay						
95	130	medium coarse sand						
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/16/2003 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/17/2003								
under the business name of Harp Well & Pump Service Inc. by (signature) <i>Jo dd S. Harp</i>								