


1 LOCATION OF WATERWELL: County: <u>Seagwick</u> Fraction: <u>NW 1/4 SE 1/4 SE 1/4</u> Section Number: <u>25</u> Township Number: <u>T 27 S</u> Range Number: <u>R 2 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>1454 Hornecker Wichita</u>	
2 WATER WELL OWNER: <u>Mike Whitworth</u> RR#, St. Address, Box # : City, State, ZIP Code : Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL <u>126</u> ft. ELEVATION: ft. Depth(s) Groundwater Encountered <u>25</u> ft. 2 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr <u>11-7-03</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>20</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: <u>1</u> Domestic 2 Irrigation 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>
5 TYPE OF BLANK CASING USED: <u>2</u> Steel 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>2</u> PVC 3 RMP (SR) 9 Other (specify below) Welded 4 ABS 7 Fiberglass Threaded Blank casing diameter in. to <u>116</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>1600psi</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole) SCREEN-PERFORATED INTERVALS: From <u>116</u> ft. to <u>126</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>25</u> ft. to <u>126</u> ft., From ft. to ft.	
6 GROUT MATERIAL: <u>3</u> 1 Neat cement <u>25</u> 2 Cement grout <u>3</u> 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>25</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) <u>3</u> Sewer lines 5 Cess pool 6 Seepage pit Direction from well? <u>east</u> How many feet? <u>60</u>	
FROM TO LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 3 top soil	
3 15 clay	
15 30 fine sand	
30 95 clay	
95 110 fine sand	
110 126 med gravel	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-7-03</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>11-7-03</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Michael Groggs</u>	