

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Seelywick</u>		<u>NE 1/4 SW 1/4 SW 1/4</u>	<u>26</u>	T <u>27</u> <u>S</u>	R <u>2</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1355 S. Pawmwood Ct.</u>					
2 WATER WELL OWNER:					
RR#, St. Address, Box # : City, State, ZIP Code :			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL <u>80</u> ft. ELEVATION: <u>80</u> ft.		
			Depth(s) Groundwater Encountered <u>1</u> ft. 2 <u>30</u> ft. 3 <u>8-31-04</u> ft.		
			WELL'S STATIC WATER LEVEL <u>30</u> ft. below land surface measured on mo/day/yr		
			Pump test data: Well water was <u>25</u> ft. after <u>25</u> hours pumping <u>25</u> gpm		
			Est. Yield <u>25</u> gpm: Well water was <u>25</u> ft. after <u>25</u> hours pumping <u>25</u> gpm		
WELL WATER TO BE USED AS:			5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7 Domestic (lawn & garden)</u> 10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? <u>Yes</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
<u>2 PVC</u>		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter <u>5</u> in. to <u>23</u> ft., Dia <u>2.40</u> in. to <u>160 psi</u> lbs./ft. Wall thickness or gauge No.					
Casing height above land surface <u>12</u> in., weight <u>2.40</u> lbs./ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass		4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		<u>3</u> Mill slot	5 Guazed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>23</u> ft. to <u>80</u> ft., From <u>23</u> ft. to <u>80</u> ft.					
GRAVEL PACK INTERVALS: From <u>30</u> ft. to <u>80</u> ft., From <u>30</u> ft. to <u>80</u> ft.					
6 GROUT MATERIAL:					
1 Neat cement		<u>2</u> Cement grout	3 Bentonite	4 Other	
Grout Intervals: From <u>3</u> ft. to <u>30</u> ft., From <u>30</u> ft. to <u>80</u> ft., From <u>30</u> ft. to <u>80</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
<u>3 Watertight sewer lines</u>		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>North</u>				How many feet? <u>60 ft</u>	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>1</u>	<u>Top soil</u>			
<u>1</u>	<u>30</u>	<u>Clay</u>			
<u>30</u>	<u>33</u>	<u>Fine Sand</u>			
<u>33</u>	<u>80</u>	<u>Shale</u>			
RECEIVED					
SEP 07 2004					
BUREAU OF WATER					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-31-04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>9-2-04</u> under the business name of <u>Weninger Drilling inc.</u> by (signature) <u>E. J. [Signature]</u>					