


1 LOCATION OF WATER WELL: Fraction S 1/4 NE 1/4 Section Number 14 Township Number 27 Range Number 20
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? 34 N. Arsanben Ct.

2 WATER WELL OWNER: Paul Sangraski
 RR#, St. Address, Box #: Paul Sangraski
 City, State, ZIP Code: Paul Sangraski
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 62 ft. ELEVATION: 9-7-04 ft.
 Depth(s) Groundwater Encountered 15 ft. 2 9-7-04 ft.
 WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 9-7-04
 Pump test data: Well water was 25 gpm: Well water was 25 ft. after 25 hours pumping 25 gpm
 Est. Yield 25 gpm: Well water was 25 ft. after 25 hours pumping 25 gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 Blank casing diameter 5 in. to 12.52 ft., Dia 24 in. to 160 ft.
 Casing height above land surface 12.52 in., weight 24 lbs./ft. Wall thickness or gauge No. 160
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 25 ft.
 SCREEN-PERFORATED INTERVALS: From 52 ft. to 62 ft., From 15 ft. to 62 ft.
 GRAVEL PACK INTERVALS: From 15 ft. to 62 ft., From 15 ft. to 62 ft.

6 GROUT MATERIAL: 3 Neat cement 15 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 15 ft., From 15 ft. to 62 ft., From 62 ft. to 62 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? North
 How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	topsoil			
1	20	clay			
20	33	med sand			
33	35	clay			
35	39	fine sand			
39	62	med sand			

RECEIVED
 OCT 04 2004
 BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-7-04 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's Licence No. 38 This Water Well Record was completed on (mo/day/yr) 9-10-04
 under the business name of Weninger Drilling Inc. by (signature) Dickie Grogg