

1 LOCATION OF WATER WELL: County: Sedgwick NE Section Number: 26 Township Number: 20 Range Number: 20

Distance and direction from nearest town or city street address of well if located within city: 1327 S. Fairwood Ct.

2 WATER WELL OWNER: RR#, St. Address, Box #: Wichita Water Boys City, State, ZIP Code: Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in SW corner]

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 89.01 ft.

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued, Clamped, Welded, Threaded.

Blank casing diameter: 12 in. to 25 in. Dia. 2.90 in. to 100 in. Dia.

Casing height above land surface: 12 in., weight: 2.90 lbs./ft. Wall thickness or gauge No. 100.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole).

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Guazed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole).

SCREEN-PERFORATED INTERVALS: From 0 ft. to 80 ft., From 80 ft. to 100 ft., From 100 ft. to 120 ft., From 120 ft. to 140 ft., From 140 ft. to 160 ft., From 160 ft. to 180 ft., From 180 ft. to 200 ft., From 200 ft. to 220 ft., From 220 ft. to 240 ft., From 240 ft. to 260 ft., From 260 ft. to 280 ft., From 280 ft. to 300 ft.

GRAVEL PACK INTERVALS: From 0 ft. to 80 ft., From 80 ft. to 100 ft., From 100 ft. to 120 ft., From 120 ft. to 140 ft., From 140 ft. to 160 ft., From 160 ft. to 180 ft., From 180 ft. to 200 ft., From 200 ft. to 220 ft., From 220 ft. to 240 ft., From 240 ft. to 260 ft., From 260 ft. to 280 ft., From 280 ft. to 300 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other.

Grout Intervals: From 0 ft. to 250 ft., From 250 ft. to 300 ft., From 300 ft. to 350 ft., From 350 ft. to 400 ft., From 400 ft. to 450 ft., From 450 ft. to 500 ft., From 500 ft. to 550 ft., From 550 ft. to 600 ft., From 600 ft. to 650 ft., From 650 ft. to 700 ft., From 700 ft. to 750 ft., From 750 ft. to 800 ft., From 800 ft. to 850 ft., From 850 ft. to 900 ft., From 900 ft. to 950 ft., From 950 ft. to 1000 ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below).

Direction from well? west How many feet? 30

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 3 topsoil

3 80 broken shale

RECEIVED

OCT 04 2004

BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-10-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 91004 This Water Well Record was completed on (mo/day/yr) 9-10-04 under the business name of Manning Drilling Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 4000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.