

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 SE 1/4 NW 1/4	28	T 27S S	R 24W E/W
Distance and direction from nearest town or city street address of well if located within city? 2526 St. Andrew Ct.					
2 WATER WELL OWNER: Bob Stamper					
RR#, St. Address, Box # : 2526 St. Andrew Ct.			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Goddard, KS			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 90 ft. ELEVATION: 90			
N - - NW - - NE - - - - X - - W - - E - - SW - - SE - - S		Depth(s) Groundwater Encountered 19 19 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 4/18/05			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Welded			
		Threaded			
Blank casing diameter 5 in. to 90 ft. Dia 100 in. to 26					
Casing height above land surface 16 in., weight 100 lbs./ft. Wall thickness or gauge No. 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement					
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)					
		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
		7 Torch cut 10 Other (specify) ft.			
SCREEN-PERFORATED INTERVALS: From 50 ft. to 90 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 90 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? South		How many feet? 15			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	19	clay			
19	31	fine sand			
31	42	green shale			
42	61	blue shale			
61	64	red shale			
64	90	blue shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/18/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 611 This Water Well Record was completed on (mo/day/yr) 4/30/05 under the business name of Chase Drilling by (signature) R. Chase					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					