


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>NE 1/4 SW 1/4 SW 1/4</u>	Section Number <u>26</u>	Township Number <u>T 27 S</u>	Range Number <u>R 2W E/W</u>
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

15001 W. Lynndale2 WATER WELL OWNER: Paul & Dennise OldlandRR#, St. Address, Box # : 15001 W. LynndaleCity, State, ZIP Code : Wichita, KSBoard of Agriculture, Division of Water Resources
Application Number:3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 90 ft. ELEVATION:

AN "X" IN SECTION BOX:

Depth(s) Groundwater Encountered 25 ft. 2 25 ft. 3 25 ft.WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yrPump test data: Well water was 25 ft. after 25 hours pumping 25 gpmEst. Yield 25 gpm: Well water was 25 ft. after 25 hours pumping 25 gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR)

2 PVC 4 ABS

6 Asbestos-Cement

7 Fiberglass

9 Other (specify below)

Welded

Threaded

Blank casing diameter 5 in. to 90 ft. Dia 16 in. to 100 ft. Dia 26 in. to 26 ft.Casing height above land surface 16 in., weight 100 lbs./ft. Wall thickness or guage No. 26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless Steel

5 Fiberglass

7 PVC

8 RMP (SR)

10 Asbestos-Cement

11 Other (Specify)

12 None used (open hole)

2 Brass

4 Galvanized Steel

6 Concrete tile

9 ABS

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Guazed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

10 Other (specify) 26 ft.SCREEN-PERFORATED INTERVALS: From 80 ft. to 90 ft. From 80 ft. to 90 ft. From 80 ft. to 90 ft.GRAVEL PACK INTERVALS: From 25 ft. to 90 ft. From 25 ft. to 90 ft. From 25 ft. to 90 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 4 ft. to 25 ft. From 25 ft. to 90 ft. From 25 ft. to 90 ft. From 25 ft. to 90 ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well? NorthHow many feet? 18

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 topsoil

2 15 clay

15 20 Fine sand

20 41 clay

41 79 med sand

79 90 med gravel

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on (mo/day/year) 5-2-02 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's Licence No 5-23-05 This Water Well Record was completed on (mo/day/yr) 5-23-05under the business name of Chase Drilling by (signature) R. Chase