

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 SW 1/4 SE 1/4	SECTION NUMBER 26	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 2W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

14101 Monterey		Wichita, Kansas	
2	WATER WELL OWNER:	ROBL CONSTRUCTION	
	RR#,ST. ADDRESS,BOX #:	5842 W. 21st St. N.	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	Application Number:
		ZIP CODE:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W E

N

NW NE

S

SW SE

4 DEPTH OF COMPLETED WELL: 98 ft. ELEVATION: _____

Depth of groundwater Encountered: _____ ft.

WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 3/7/06

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter 12 in. to 98 ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic

2. Irrigation

3. Feedlot

4. Industrial

5. Public water supply

6. Oil field water supply

7. Lawn and garden only

8. Air conditioning

9. Dewatering

10. Monitoring well

11. Injection well

12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO

Was Water Well Disinfected? _____ YES NO

If yes, what mo/day/yr was sample _____

5		TYPE OF CASING USED:		1. Steel		3. RPM (SR)		5. Wrought Iron		7. Fiberglass		9. Other (Specify below)		CASING JOINTS: <u>Glued</u>		Threaded					
		2. <u>PVC</u>		4. ABS		6. Asbestos-Cement		8. Concrete tile		SDR-26				Welded		Clamped					
Blank casing diameter		5		in.		to		40		ft.,		Dia.		in.		to		ft.			
Casing height above land surface:		12		in.,		Weight:		2.35		lbs. / ft.		Wall thickness or gauge No.		.214							
TYPE OF SCREEN OR PERFORATION MATERIAL:		1. Steel		3. Stainless Steel		5. Fiberglass		<u>7. PVC</u>		9. ABS		11. Other (specify)									
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement		12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:		1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None (open hole)									
2. Louvered shutter		4. Key punched		6. Wire wrapped		<u>8. Saw cut</u>		10. Other (specify)													
SCREEN - PERFORATION INTERVAL		From		40		ft.		to		98		ft.,		From		ft.		to		ft.	
		From				ft.		to				ft.,		From		ft.		to		ft.	
GRAVEL PACK INTERVALS:		From		24		ft.		to		98		ft.,		From		ft.		to		ft.	
		From				ft.		to				ft.,		From		ft.		to		ft.	

6	GROUT MATERIALS:		1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug						
	Grout Intervals:	From	4 ft.	to	24 ft.,	From	35 ft.	to	40 ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:												
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well							
2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)								
3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage										
Direction from well? North													
How many feet? 15													

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **3/7/2006** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **3/10/2006**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *J o d d S. H a r p*