


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick		FRACTION SW 1/4 SW 1/4 NE 1/4		SECTION NUMBER 23	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 2W EW
Distance and direction from nearest town or city street address of well if located within city? 14216 W. Binter Circle Wichita, Kansas						
2 WATER WELL OWNER: JACOBS, Tim		Board of Agriculture, Division of Water Resource				
RR#,ST. ADDRESS,BOX #: 14216 W. Binter Circle		CITY, STATE: Wichita, Kansas		ZIP CODE:		Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION:				
		Depth of groundwater Encountered: ft. ft. ft.				
		WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 6/4/07				
		Pump test data: Well water was ft. after hours of pumping @ gpm				
Est. Yield: gpm Well water was ft. after hours of pumping @ gpm						
Bore Hole Diameter 12 in. to 110 ft. and in. to ft.						
WELL WATER TO BE USED AS:						
1. Domestic 3. Feedlot 5. Public water supply 7. <u>Lawn and garden only</u> 9. Dewatering 11. Injection well						
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)						
Was a chemical/bacteriological sample submitted to Department? YES <u>NO</u> ; If yes, what mo/day/yr was sample submitted <u>YES</u> NO						
5 TYPE OF CASING USED:						
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: <u>Glued</u> Threaded						
<u>2. PVC</u> 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped						
Blank casing diameter 5 in. to 35 ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1. Steel 3. Stainless Steel 5. Fiberglass <u>7. PVC</u> 9. ABS 11. Other (specify)						
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)						
2. Louvered shutter 4. Key punched 6. Wire wrapped <u>8. Saw cut</u> 10. Other (specify)						
SCREEN - PERFORATION INTERVAL From 35 ft. to 110 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 24 ft. to 110 ft., From ft. to ft.						
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug						
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well						
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)						
<u>3. Watertight sewer line</u> 6. Seepage pit 9. Feed yard 12. Fertilizer storage						
Direction from well? East How many feet? 15 ft						
From To LITHOLOGIC LOG From To LITHOLOGIC LOG						
0 3 topsoil						
3 27 clay						
27 35 fine sand						
35 45 medium sand						
45 110 grey shale						
7 Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 6-4-2007 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6-5-2007						
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp						