

1	LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 SW 1/4 SW 1/4	SECTION NUMBER 11	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 2W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1300 N. Blackstone St. Blackstone and 13th St., NW corner (Reserve D) Wichita, Kansas

2 WATER WELL OWNER: **KELSEY DEVELOPMENT**
 RR#,ST. ADDRESS,BOX #: **716 N. 119th St. W.**
 CITY, STATE: **Wichita, Kansas** ZIP CODE: **67212**

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

N	
NW	NE
SW	SE
S	

W E

4 DEPTH OF COMPLETED WELL: 92 ft. ELEVATION: _____ ft.

Depth of groundwater Encountered: _____ ft.

WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 11/13/08

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter 12 in. to 92 ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic	3. Feedlot	5. Public water supply	7. <u>Lawn and garden only</u>	9. Dewatering	11. Injection well
2. Irrigation	4. Industrial	6. Oil field water supply	8. Air conditioning	10. Monitoring well	12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted _____

Was Water Well Disinfected? YES NO

5 TYPE OF CASING USED:				CASING JOINTS:				☒ Glued ☐ Welded ☐ Threaded ☐ Clamped					
1. Steel		3. RPM (SR)		5. Wrought Iron		7. Fiberglass		9. Other (Specify below)		SDR-26			
☒ 2. PVC		4. ABS		6. Asbestos-Cement		8. Concrete tile							
Blank casing diameter		5 in.		to 62 ft.,		Dia.		in.		to		ft.,	
Casing height above land surface:		12 in.,		Weight:		2.35 lbs. / ft.		Wall thickness or gauge No.		.214			
TYPE OF SCREEN OR PERFORATION MATERIAL:													
1. Steel		3. Stainless Steel		5. Fiberglass		☒ 7. PVC		9. ABS		11. Other (specify)			
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement		12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:													
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None (open hole)			
2. Louvered shutter		4. Key punched		6. Wire wrapped		☒ 8. Saw cut		10. Other (specify)					
SCREEN - PERFORATION INTERVAL		From		62 ft.		to		92 ft.,		From		ft.	
		From		ft.		to		ft.,		From		ft.	
GRAVEL PACK INTERVALS:		From		24 ft.		to		92 ft.,		From		ft.	
		From		ft.		to		ft.,		From		ft.	

6	GROUT MATERIALS:		1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug		
	Grout Intervals:	From	4 ft.	to	24 ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:								
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well			
2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)				
3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage						
Direction from well?		North		How many feet? 10 ft. plus					

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **11/13/2008** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **11/17/2008**
under the business name of **Harp Well and Pump Service** by (signature) *Todd S. Harp*