

1

LOCATION OF WATER WELL:

County:

Sedgewick, OK

Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here

405 S Fawnwood St  
Wichita, KS 67235

2

WATER WELL OWNER:

RR#, Street Address, Box #:

Jake McCabe  
405 S Fawnwood St  
Wichita, KS 67235

3

LOCATE WELL WITH AN "X" IN SECTION BOX:

N

W

E

S

X

1 mile

4

DEPTH OF COMPLETED WELL

90

ft.

Depth(s) Groundwater Encountered (1)

ft.

(2)

ft.

(3)

ft.

WELL'S STATIC WATER LEVEL

25

ft. below land surface measured on mo/day/yr.

4-25-11

Pump test data: Well water was

ft. after

hours pumping

gpm

EST. YIELD

30

gpm. Well water was

ft. after

hours pumping

gpm

Bore Hole Diameter

12

in. to

90

ft., and

in. to

ft.

WELL WATER TO BE USED AS:

Public water supply

Geothermal

Injection well

Domestic

Feedlot

Oil field water supply

Dewatering

Other (Specify below)

Irrigation

Industrial

Domestic-lawn & garden

Monitoring well

Was a chemical/bacteriological sample submitted to Department?

Yes

No

If yes, mo/day/yr sample was submitted

Water well disinfected?

Yes

No

5

TYPE OF CASING USED:

Steel

PVC

Other

CASING JOINTS:

Glued

Clamped

Welded

Threaded

Casing diameter

5

in. to

39

ft., Diameter

in. to

ft., Diameter

in. to

ft.

Casing height above land surface

12

in., Weight

2.4

lbs./ft., Wall thickness or gauge No.

11.60 psi

TYPE OF SCREEN OR PERFORATION MATERIAL:

Steel

Stainless Steel

PVC

Other (Specify)

Brass

Galvanized Steel

None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

Continuous slot

Mill slot

Gauze wrapped

Torch cut

Drilled holes

None (open hole)

Louvered shutter

Key punched

Wire wrapped

Saw cut

Other (specify)

SCREEN-PERFORATED INTERVALS:

From

30

ft. to

95

ft., From

ft. to

ft.

From

ft. to

ft., From

ft. to

ft.

GRAVEL PACK INTERVALS:

From

25

ft. to

95

ft., From

ft. to

ft.

From

ft. to

ft., From

ft. to

ft.

6

GROUT MATERIAL:

Neat cement

Cement grout

Bentonite

Other

Grout Intervals:

From

3

ft. to

25

ft., From

ft. to

ft., From

ft. to

ft.

What is the nearest source of possible contamination:

Septic tank

Lateral lines

Pit privy

Livestock pens

Insecticide storage

Other (specify below)

Sewer lines

Cesspool

Sewage lagoon

Fuel storage

Abandoned water well

Watertight sewer lines

Seepage pit

Feedyard

Fertilizer storage

Oil well/gas well

Direction from well

South

Distance from well

12

FROM

TO

LITHOLOGIC LOG

FROM

TO

LITHO. LOG (cont.) or PLUGGING INTERVALS

0

3

Top Soil

3

25

Clay

25

30

Fine Sand

30

95

Blue Shale

7

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:

This water well was

constructed

reconstructed

plugged

under my jurisdiction and was completed on (mo/day/year)

5-1-11

and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No.

240

This Water Well Record was completed on (mo/day/year)

5-30-11

under the business name of

William J. Sully, Jr.

by (signature)

William J. Sully, Jr.

INSTRUCTIONS:

Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420 Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.