WATER WELL RECORD Form WWC-5 KSA 82a-1212 RANGE NUMBER LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER Sedgwick NE NWSE 28 27 S 2WE/W 1/4 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? **Behind 2105 Sunset** Goddard, Kansas DOVE ESTATES WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1400 S. 163rd Rd West ZIP CODE: 67052 CITY, STATE: Goddard, Kansas Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: ft. ft, ft. Depth of groundwater Encountered: 18 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm ΝE ΝW Est. Yield: hours of pumping @ gpm Well water was ft. after apm ⋽ 12 to 100 Bore Hole Diameter in. to ft. and WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 3. Feedlot 5. Public water supply 7. Lawn and garden only 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) NO submitted Was Water Well Disinfected? TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 33 ft., Dia ft. Blank casing diameter ft.. Dia. in. to in. to Casing height above land surface: 12 Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 3. Stainless Steel 5. Fiberglass 1 Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped SCREEN - PERFORATION INTERVAL 33 ft 100 to ft., From From ft to ft. ft. From to ft . From ft tο ft GRAVEL PACK INTERVALS: 24 ft. 100 From ft.. From ft to ft. From ft. to ft.. From ft **GROUT MATERIALS:** Other bentonite hole plug 6 3. Bentonite 2. Cement Grout 1. Neat cement Grout Intervals: ft. 24 ft., From ft to From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2 Sewer lines 12. Fertilizer storage 6. Seepage pit 9. Feed yard 3. Watertight sewer line North How many feet? 100 ft. plus Direction from well? From LITHOLOGIC LOG From Τo LITHOLOGIC LOG Tο 0 3 topsoil 3 18 clay 18 36 medium sand 36 100 gray shale under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. **constructed** 2. **reconstructed** or plugged

was completed on (mo/day/year)

4/8/2014

and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

4/11/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb