


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County <u>Sedg</u>	Fraction <u>SW 1/4 SW 1/4 NW 1/4</u>	Section number <u>34</u>	Township number <u>T 27 S</u>	Range number <u>R 2 E</u>
2. Distance and direction from nearest town or city: <u>3 E Goddard 1/4 So.</u> Street address of well location if in city:				3. Owner of well: <u>Lowell Nicholson</u> R.R. or street: <u>RR #2 167th St. West.</u> City, state, zip code: <u>Goddard KS 67052</u>		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. <u>5 1/4</u> in. Completion date <u>1/12/76</u> Well depth <u>50</u> ft.		
				7. ☐ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
5. Type and color of material				From	To	8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other
<u>Top soil</u>				<u>0</u>	<u>3</u>	9. Casing: Material <u>plastic</u> Height: Above or below Threaded ☐ Welded ☒ Surface <u>12</u> in. RMP ☐ PVC ☒ Weight <u>231</u> lbs./ft. Dia. <u>5</u> in. to <u>50</u> ft. depth Wall Thickness: inches or Dia. <u>5</u> in. to <u>50</u> ft. depth gage No. <u>200</u>
<u>black grayish clay</u>				<u>3</u>	<u>13</u>	10. Screen: Manufacturer's name <u>JTL</u> Type <u>Plastic RMP</u> <u>5</u> in. Slot/gauze <u>1/16</u> Length <u>15</u> ft. Set between <u>40</u> ft. and <u>50</u> ft. <u>25</u> ft. and <u>30</u> ft. Gravel pack? <u>yes</u> Size range of material <u>3/8</u>
<u>Reddish clay</u>				<u>13</u>	<u>18</u>	11. Static water level: <u>18</u> ft. below land surface Date <u>1/12/76</u>
<u>fine to coarse gravel</u>				<u>18</u>	<u>26</u>	12. Pumping level below land surfaces: <u>22</u> ft. after <u>1</u> hrs. pumping <u>18</u> g.p.m. <u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m. Estimated maximum yield <u>40</u> g.p.m.
<u>grayish clay to gray shale</u>				<u>26</u>	<u>50</u>	13. Water sample submitted: <u> </u> mo./day/yr. <u> </u> Yes ☒ No Date <u> </u>
						14. Well head completion: ☒ Pitless adapter <u>12</u> inches above grade
						15. Well grouted? <u>yes</u> With: <u> </u> Neat cement ☒ Bentonite <u> </u> Concrete Depth: From <u>3</u> ft. to <u>13</u> ft.
						16. Nearest source of possible contamination: <u>100</u> ft. Direction <u>West</u> Type <u>Septic</u> Well disinfected upon completion? ☒ Yes <u> </u> No
						17. Pump: Manufacturer's name <u>Valley</u> Not installed Model number <u>1807</u> HP <u>1/2</u> Volts <u>230</u> Length of drop pipe <u>40</u> ft. capacity <u>18</u> g.p.m. Type: ☒ Submersible <u> </u> Turbine <u> </u> Jet <u> </u> Reciprocating <u> </u> Centrifugal <u> </u> Other
(Use a second sheet if needed)						
18. Elevation:		19. Remarks:		20. Water well contractor's certification:		
Topography: <u> </u> Hill <u> </u> Slope ☒ Upland <u> </u> Valley		<u>Customer to complete 4x4x4 concrete slab. He knows this is regulation</u> <u>Lowell Nicholson</u>		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Weninger Drilling</u> <u>318</u> Business name License No. Address <u>Colwich</u> Signature <u>JC Weninger</u> Date <u>1/12/76</u> Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5