


1 LOCATION OF WATER WELL: County SEDGWICK		Fraction SW 1/4 SW 1/4 SE 1/4	Section Number 33	Township Number T 27 S	Range Number R 2W 1E
Distance and direction from nearest town or city street address of well if located within city? 1/2 West of Colwich Road, 1 So. of Highway 54 North Side . Goddard, Kansas					
2 WATER WELL OWNER: Alan Edwards RR#, St. Address, Box # : 1618 West 22nd North City, State, ZIP Code : Wichita, Kansas		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:ft. Depth(s) Groundwater Encountered 1. 23ft. 2.ft. 3.ft. WELL'S STATIC WATER LEVEL 23ft. below land surface measured on mo/day/yr 1-18-83 Pump test data: Well water wasft. after hours pumping gpm Est. Yield gpm: Well water wasft. after hours pumping gpm Bore Hole Diameter 11in. toft., andin. toft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued .. X .. Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5in. to 20ft., Diain. toft., Diain. toft. Casing height above land surface 12in., weight 1.59lbs./ft. Wall thickness or gauge No. 203 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20ft. to 50ft., Fromft. toft. GRAVEL PACK INTERVALS: From 14ft. to 50ft., Fromft. toft. Fromft. toft., Fromft. toft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 40ft. to 14ft., Fromft. toft., Fromft. toft. What is the nearest source of possible contamination: None Apparent 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG 0 3 Topsoil 3 21 Clay 03 21 27 Fine Sand 07 27 50 Gray Shale 19					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-18-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 3-18-83 under the business name of Harp Well & Pump Service, Inc. by (signature) M. Arnold INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

27

R

2

EW

SEC.

33

SD 1/4

SD 1/4

SD 1/4

SD 1/4