WATER WELL RECORD Form WWC-5 KSA 82a-1212 TOWNSHIP NUMBER RANGE NUMBER LOCATION OF WATER WELL: FRACTION SECTION NUMBER 2WE/W NE NE SW24 27 R Sedgwick Т S 1/4 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 201 N. Rainbow Lake Road Wichita, Kansas JANTZ, Chad WATER WELL OWNER: Board of Agriculture, Division of Water Resource 201 N. Rainbow Lake Road RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: 97 **ELEVATION:** ft. LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: WITH AN "X" IN SECTION BOX: ft ft. Depth of groundwater Encountered: ft. 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/9/14 WELL'S STATIC WATER LEVEL Pump test data: Well water was ft. after hours of pumping @ gpm NEft. after hours of pumping @ gpm Est. Yield: Well water was gpm Φ to 97 ≌ Bore Hole Diameter 12 ft. and in. ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE-SW 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? YES Was Water Well Disinfected? YES NO submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 77 Dia. ft., Dia. ft. Blank casing diameter in. in. to to 12 in., Weight: 2.35 Wall thickness or gauge No. .214 Casing height above land surface: lbs. / ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ARS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 7. Torch cut 1. Continuous slot 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 97 SCREEN - PERFORATION INTERVAL 77 ft. From to ft. From ft. to ft. ft to ft., From From ft. to ft. 24 ft. to 97 **GRAVEL PACK INTERVALS:** ft., From ft. to From ft. From ft. to ft... From ft. to ft GROUT MATERIALS: Other bentonite hole plug 6 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From ft 24 ft.. ft. ft. From ft. From to ft., What is the nearest source of possible contamination: 15. Oil well/Gas well 10. Livestock pens 13. Insecticide storage 7. Pit privy 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line How many feet? 10 ft. plus West Direction from well? LITHOLOGIC LOG From LITHOLOGIC LOG From Τо Τо Ω topsoil 30 clay 30 fine sand 45 clay 82 medium sand 95 97 clay

under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or plugged 9/9/2014 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) This water well record was completed on (mo/day/year) 9/11/2014 Kansas Water Well Contractor's License No. 236

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb