WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER 1 LOCATION OF WATER WELL: FRACTION TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE SE SW 11 27 2W 1/4 1/4 1/4 Т S E/W Distance and direction from nearest town or city street address of well if located within city? 1436 N. Blackstone Wichita, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10008 W.York Wichita, Kansas ZIP CODE: 67235 CITY, STATE: Application Number 66 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/21/14 Pump test data: Well water was ft. after hours of pumping @ -NW NE gpm **⊠** Est. Yield: Weil water was apm ft. after hours of pumping @ gpm 12 Bore Hole Diameter to 66 in and ft. WELL WATER TO BE USED AS: 11. Injection well 5. Public water supply 7. Lawn and garden only 3₩ SE 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (\$R) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 45 Dia Dia. in. ft. to 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 3. Stainless Steel 5 Fiberolass 1. Steel 6. Concrete Tile 8. RMP (SR) 2. Brass 4. Galvanized 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 10. Other (specify) 4. Key punched 6. Wire wrapped SCREEN - PERFORATION INTERVAL 65 45 ft. From to ft., From ft. ft to ft. From to ft., From ft ft. to 24 **GRAVEL PACK INTERVALS:** to 65 From ft., From ft. From ft. to ft., From ft tο ft. **GROUT MATERIALS:** 6 Other 2. Cement Grout bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: 24 From ft., ft. to ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 3 Watertight sewer line 6. 9. Feed yard 12. Fertilizer storage 6. Seepage pit Direction from well? How many feet? 10 ft. plus From LITHOLOGIC LOG Tο From To LITHOLOGIC LOG topsoil 38 clav 38 fine sand 45 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 7/21/2014 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) Todd S. Harb under the business name of Harp Well and Pump Service by (signature)