WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: TOWNSHIP NUMBER SECTION NUMBER RANGE NUMBER FRACTION Sedawick NE 2.7 S R 2W F/W

Beugwick	1430 1/4	511	1/4 131	<i>□</i> 1/4		1	Ad I	J	1 2 4	* L/VV
Distance and direction from nearest town or city s	treet address of we	ll if located wi	thin city?		and a recommendation of the control	CONTRACTOR MANAGEMENT OF THE PARTY OF THE PA				
Behind 1925 N. Bellick Ct.	Reserve C.		Wichita	, Kans	as					
	ERTON HO							Doord of Agr	iculture, Division of \	Mater Pessures
	V. 119th W.	Unit 112						boald of Agr	iculture, Division or v	water Nesource
CITY, STATE: Wich	ita, Kansas				ZIP C	ODE:	WHENEYE STATE OF THE STATE OF T	Application Nur	nber:	
3 LOCATE WELL'S LOCATION 4 D	EPTH OF COM	PLETED WE	ELL:	67	ft.	ELE/	/ATION:			
N Dep	th of groundwate	er Encounter	ed:		ft.			ft.		ft.
WE ! WE	LL'S STATIC W	ATER LEVE	L 30	FT.	BELOW L	AND SURFAC	E MEASU	RED ON mo/o	day/yr: 10 /3	3/14
NMNE	Pt	ımp test dat	a: Well	water wa	as	ff	t. after	hours	s of pumping @	gpr
	Est. Yield:	gpm	Well	water wa	as	f	t. after	hours	s of pumping @	gpn
firm	re Hole Diamete		in.		to 67	ft.	and	in.	to	ft.
	LL WATER TO						udan anli	9. Dewateri	ing ,	ction well
		Feedlot				Lawn and ga	_ :	ر 10. Monito rii		pecify below
	Irrigation 4 as a chemical/bact	. Industrial			1-13	Air condition	NO		mg wen what mo/day/yr	was sample
,	mitted	anological san	spie subiriitieu	то Берап	unent	YES C Was Water \				NO
5 TYPE OF CASING USED:	E \\/\na_1.ch	4 lean	7. Fibergla		9 Other	(Specify below	v) CASI	NG JOINTS:	Glued	Threaded
1. Steel 3. RPM (SR	5. Wrough	IL HON	r. Fibergia	155	SDR-2		.,		Welded	Clamped
2. PVC 4. ABS	6. Asbesto	s-Cement	8. Concret	te tile	SDR-2	.0				
Blank casing diameter 5 i	n. to	47 ft.,	Dia.		in.	to	ft., C	Dia.	in. to	ft.
Casing height above land surface:	12 in.,		Weight:	2.3	5 lbs./	ft.	Wall thic	ckness or gau	ge No214	ļ
TYPE OF SCREEN OR PERFORATION	MATERIAL:									
Steel 3. Stainless Steel	Fiberglass	s <	7. PVC		9. ABS		11. Oth	er (specify)		
2. Brass 4. Galvanized	Concrete	Tile	8. RMP (SI	₹)	10. Asbe	stos-Cement	12. Nor	ne used (open	hole)	
SCREEN OR PERFORATION OPENING	S ARE:									
1. Continuous slot 3. Mill slo	ot 5.	Gauzed wr	apped		7. Torch	cut	9. Drille	d holes	11. None (open hole)
2. Louvered shutter 4. Key pu	nched 6.	Wire wrap	ped	<	8. Saw c	ut	10. Othe	r (specify)		
SCREEN - PERFORATION INTERVAL	From	47	ft.	to	67 ft.	, Fr	rom	ft.	to	ft.
	From		ft.	to	ft.	. Fi	rom	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24	ft.	to	67 ft.		rom	ft,	to	ft.
	From		ft.	to	ft.		rom	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat of		2 Cam	ent Grout			entonite			tonite hole pl	
Grout Intervals: From 4	ft. to		ft From	m	ft	to	ft	From	ft. to	O .
		- 1	1101	1.7	11.	11.7	DL.	ETOHI	14. 11.	, !!

What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 5. Cess Pool 3. Watertight sewer line Direction from well? North		7. Pit privy 8. Sewage lagoon	10. Livestoo	•	13. Insecticide storage14. Abandon water well	15. Oil well/Gas well 16. Other (specify below)	
		9. Feed yard	12. Fertilize	r storage	How many feet? 10 ft. plus		
From	То	LITHOLO	GIC LOG	From	То	LITHOLOG	GIC LOG
00	3	topsoil					The state of the s
3	28	clay					
28	45	fine sand					
45	67	medium sand					
							·····
			·				
					 		
					<u> </u>		

			······································				

under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged 10/3/14 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) This water well record was completed on (mo/day/year) 10/6/2014 Kansas Water Well Contractor's License No. 236

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp