Form WWC-5 KSA 82a-1212 WATER WELL RECORD 1 LOCATION OF WATER WELL: RANGE NUMBER SECTION NUMBER TOWNSHIP NUMBER FRACTION 27 2WE/W NW SE SW 11 T S 1/4 Sedgwick, 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 14505 W. Price Wichita, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10008 W. York Wichita, Kansas Application Number: CITY, STATE: ZIP CODE 70 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft ft. ft. Depth of groundwater Encountered: FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: WELL'S STATIC WATER LEVEL 25 Pump test data: Well water was ft. after hours of pumping @ gpm NE NW ft. after hours of pumping @ gpm Well water was Est. Yield: apm ø to 70 12 to ft. Bore Hole Diameter ft. in. Ī in. and 11. Injection well WELL WATER TO BE USED AS: 9. Dewatering 5. Public water supply 7. Lawn and garden only SE SW 3. Feedlot 1. Domestic 12. Other (Specify below) 8. Air conditioning 10. Monitoring well 6. Oil field water supply 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample (NO Was a chemical/bacteriological sample submitted to Department? S (YES) NO Was Water Well Disinfected? submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 4. ABS 2. PVC 5 45 Dia. to Dia ft. Blank casing diameter Wall thickness or gauge No. Weight: lbs. / ft. Casing height above land surface: in.. TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9 ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 12. None used (open hole) 8. RMP (SR) 10. Asbestos-Cement 4 Galvanized 6. Concrete Tile 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 11. None (open hole) 5. Gauzed wrapped 7. Torch cut 9 Drilled holes 1. Continuous slot 3. Mill slot 8. Saw cut 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped 70 45 ft ft.. From SCREEN - PERFORATION INTERVAL From to ft. ft. to ft ft., From to ft. ft. From to 24 ft. 70 GRAVEL PACK INTERVALS: to ft.. From ft ft. From tο ft. to ft., From From ft. Other bentonite hole plug GROUT MATERIALS 3. Bentonite 1. Neat cement 2. Cement Grout Grout Intervals: From 4 ft. 24 ft., ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 7. Pit privy 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Tο From Τо topsoil 3 U 23 clay 3 23 50 fine sand 55 50 clay **70** medium sand 55 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and plugged

was completed on (mo/day/year) 12/22/2014 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/23/2014