WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick SW 1/4 NE 1/4 SW	1/4 23	T 27 S	R 2W E/W
Distance and direction from nearest town or city street address of well if located within city?			
205 Fawnwood Ct. Wichita, Kansas 2 WATER WELL OWNER: BLUE CUSTOM HOMES LLC			
2 WATER WELL OWNER: BLUE CUSTOM HOMES LLC RR#,ST. ADDRESS,BOX #: 106 S. Breezy Pointe Circle		Board of Agr	riculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nu	nher:
		ELEVATION:	noer.
WITH AN "X" IN SECTION BOX:	ft.		4
N Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 35		ft.	ft.
		JRFACE MEASURED ON mo/	
Pump test data: Well war out to be set at the set of th			s of pumping @ gpm s of pumping @ gpm
Est. Yield: gpm Well wa	to 116 ft.		to ft.
₩ELL WATER TO BE USED AS:		- 9 Dewater	44 1-141 11
1. Domestic 3. Feedlot 5. Public wa	ter supply 7. Lawn a	and garden only	12. Other (Specify below)
	ater supply 8. Air con		_
S Was a chemical/bacteriological sample submitted to I submitted		NO ; If yes, Vater Well Disinfected?	what mo/day/yr was sample YES NO
5 TYPE OF CASING USED: 5 Wrought Iron 7 Fiberglass		· · · · · · · · · · · · · · · · · · ·	
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS:	Glued Threaded Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete to	le SDR-26		vveided Clamped
Blank casing diameter 5 in. to 50 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:		Train unstances on gas	30.10. 1214
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer	ment 12. None used (open	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
	116 ft.	_	
	,	From ft.	to ft.
24	,	From ft.	to ft.
	,,,,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	tonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:	ft. to	ft., From	ft. to ft.
1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
_ · ·	1. Fuel storage	14. Abandon water well	16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage			
Direction from well? East	-	How many feet? 50	ft. plus
From To LITHOLOGIC LOG	From To		OGÍC LOG
0 3 topsoil			
3 25 clay			
25 35 fine sand & clay mix			
35 70 grey shale			· · · · · · · · · · · · · · · · · · ·
100 116 grey shale			
	 		
		<u> </u>	
Contractor's or Landowner's Certification: This water well was 1. constructed	2. reconstructed	l or 3. plugged	under my jurisdiction and
was completed on (mo/day/year) 3/27/2015 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/30/2015			
under the business name of Harp Well and Pump Service	by (signature)	Todd S	. Harp