		WATER WE	LL RECORD	Form	WWC-5	KSA 82a-12	:12		
1 LOCATION OF WATER	R WELL:	FRACTION			SECTION NUM	BER TOWNSH	IP NUMBER	RANGE N	IUMBER
Sedgwick		SW 1/4	SW 1/4	NE 1/4	11	т 2	27 s	R 21	W E/W
Distance and direction from	· ·		•						
1882 N. Kentu			Vichita, Kansa						
2 WATER WELL C		USMEYER C	ONSTRUCTI	ON			Board of Agri	culture, Division of	Water Resource
RR#,ST. ADDRESS	KESS,BUX #: 1008 W. 107K								Trator Nagouroc
				(0	ZIP CODE:		Application Nun	nber:	
3 LOCATE WELL'S LO		DEPTH OF COMPL	ETED WELL:	68	ft.	ELEVATION:			
N N		oth of groundwater I	Encountered:		ft.		ft.		ft.
	WE	ELL'S STATIC WAT	ER LEVEL 2	0 FT. E	BELOW LAND	SURFACE MEAS	URED ON mo/o	lay/yr: 5/1 :	3/15
NW	- NE	Pum	p test data: W	ell water was		ft. after	hours	of pumping @	gpn
w W	, '	Est. Yield:	0.	ell water was		ft. after	hours	of pumping @	gpm
1 1 1		ore Hole Diameter	12 in.		to 68	ft. and	in.	to	ft.
- Sw		ELL WATER TO BE			سو آگی بیات	n and garden on	9. Dewateri	ng 11. Inje	ection well
	''						كور 10. Monitori r		pecify below
		. Irrigation 4. In las a chemical/bacterion			upply 8. Air on the second sec	NO		what mo/day/yr	was sample
S		bmitted	ological sample submit	ied to Departin		ıs Water Well Disi			NO
5 TYPE OF CAS	ING USED:	5 144 111	7 5:1-	1	9. Other (Spe	cify below) CA	SING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SR	5. Wrought li	ron 7. Fibei	rgiass		ony bolow)	0	Welded	Clamped
2. PVC	> 4. ABS	6. Asbestos-	Cement 8. Cond	crete tile	SDR-26				
Blank casing diamete	er 5	in. to 4	8 ft., Di	a.	in. to	ft.,	Dia.	in. to	ft.
Casing height above	land surface:	12 _{in.,}	Weigh	nt: 2.35	lbs. / ft.	Wall t	hickness or gaug	ge No214	l
TYPE OF SCREEN C		•			155.771.		monnous or gade	.217	,
1	. Stainless Steel	5. Fiberglass	7. PVC	>	9. ABS	11. C	ther (specify)		
2. Brass 4	. Galvanized	6. Concrete Til	e 8. RMP	(SR)	10. Asbestos-0	Cement 12. N	one used (open	hole)	
SCREEN OR PERFO	DATION OBENING	CO ADE:							
1. Continuous slot			auzed wrapped		7. Torch cut	9 Dri	lled holes	11. None (onen hole)
								······································	open noic,
2. Louvered shutte	r 4. Key pu	unched 6. W	ire wrapped		8. Saw cut	10. Oti	ner (specify)		
SCREEN - PERFORA	TION INTERVAL	From	48 ft.	to 🤄	8 ft.,	From	ft.	to	ft.
		From	ft,	to	ft.,	From	ft.	to	ft.
GRAVEL PAG	CK INTERVALS:	From	24 ft.	to 🗲	8 ft.,	From	ft.	to	ft.
İ		From	ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIA	ΔI S: 4 Al4 -				· · · · · · · · · · · · · · · · · · ·				
GROUT MATERIA	ALS: 1. Neat of From 4	ft. to	2. Cement Grout		3. Benton			onite hole pl	_
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to What is the nearest source of possible contamination:								ft.	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage						15. Oil well/	Gas well		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify b								pecify below)	
3 Watertight sewe	r line 6. Seepag	ge pit 9. l	Feed yard	12. Fer	tilizer storage				
Direction from well?	West	30 p	•		-	How n	nany feet? 15	ft. plus	
From To		LITHOLOGIC	LOG	Fro	m To			GIC LOG	
0 3	topsoil								
	clay								·
15 45	fine sand								
45 68	medium sand					_			
						_			
					-	···			
	ļ								
	L								
Contractor's or L	andowner's Certific	cation: This water w	ell was 1. consti	ructed 2	reconstruc	ted or 3.	plugged	under my jurisdic	tion and
was completed on ((mo/day/year)	5/13/2015	and this re	ecord is true	to the best of r	ny knowledge and	belief.		
		se No. 236				-		/2015	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/15/2015 under the business name of Harp Well and Pump Service by (signature) Todal S Harb									
under the business	name of Harp	well and Pum	p Service		y (signature)	T	oaa S	. Harp)