WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.				
		OF WATER WELL:					Range Number	
Coun	ty: Sed	qwick	1/4 SW 1/4 SW 1/4		36	T 27 S	R2 □E 🗹 W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here								
from	nearest t	own or intersection: It at o	owner's address, check he	Longitude: (in decimal degrees)  Longitude: (in decimal degrees)				
				Elevation:				
					Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Jason Griner					Collection Method:			
RR#, Street Address, Box #: 2318 S. Wheatland Ct. City, State, ZIP Code : Wichita KS 67235					☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City,	State, Z	IP Code : Wichita	KS 67235					
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 120								
SECT	SECTION BOX: Depth(s) Groundwater Encountered (1).40 ft. (2)							
	N WELL'S STATIC WATER LEVEL. 40 ft. below land surface measured on mo/day/yr							
I	Pump test data: Well water was							
	EST. YIELD. 18gpm. Well water was							
W	WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well							
☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)								
SW SE D Industrial M Demostic lover & corden D Monitoring well								
Was a chemical/bacteriological sample submitted to Department?  Yes No								
S If yes, mo/day/yr sample was submitted								
1 mile  Water well disinfected?								
5 TYPE OF CASING USED: Steel PVC Other								
CASING IOINTS: M Glued   Clamped   Welded   Threaded								
Casing diameter 5 in. to 120 ft. Diameter in. to ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface 12 in., Weight 2.5 Wall thickness or gauge No								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From 60 ft. to 120 ft., From ft. to ft. to ft.								
From								
GRAVEL PACK INTERVALS: From 20 ft. to 120 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other								
What is the nearest source of possible contamination:								
	Septic ta	·		Livestock p	ens 🔲 Insecticide	storage	er (specify below)	
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well  Direction from well								
							IGGING INTERVALS	
FROM	TO	LITHOLOG	IC LUG	FROM	TO LITHO. LO	M (COIIL) OF PLU	OOLING IN LEK VALS	
0	3	Topsoil		<del></del>				
3	40 80	Clay						
80	120	Fine Sand Shale		<del></del> +				
100	120	Ullaic						
	<b></b>					<del></del>		
<b></b>	<u> </u>	•						
<b></b>								
	<b> </b>							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .05/19/2015 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No238 This Water Well Record was completed on (mo/day/year) .05/19/2015								
under th	e busine	ss name of Premier Put	mp & Well Service, Inc.		. by (signature)!	. Williams	***************************************	
INSTRUC	CTIONS:	Use typewriter or ball point per	n. <u>PLEASE PRESS FIRMLY</u> and ment. Bureau of Water. Geologic	a <u><i>PKINT</i></u> cle v Section, 10	arry. Piease till in blanks 00 SW Jackson St., Suite	e 420. Topeka. Kansa	s 66612-1367.	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								