Form WWC-5 KSA 82a-1212 WATER WELL RECORD LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NWSedgwick 1/4 SE 36 Т 27 2W1/4 S E/W Distance and direction from nearest town or city street address of well if located within city? 2102 s. Wheatland Wichita, Kansas THOMPSON, Clinton WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2102 s. Wheatland CITY, STATE: Wichita, Kansas ZIP CODE: Application Number 4 DEPTH OF COMPLETED WELL: 84 **ELEVATION:** ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft ft 30 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr. 6/3/15 Pump test data: Well water was ft. after hours of pumping @ gpm ΝW ΝE ft. after gpm Well water was hours of pumping @ gpm ₫ 12 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES) TYPE OF CASING USED: 5 CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1 Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 55 Blank casing diameter in. to ft... Dia. in. to Dia to ft. Casing height above land surface: 12 Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 55 ft. to ft.. From From ft. to From ft. to ft... From ft. ft. GRAVEL PACK INTERVALS: 24 ft. to From ft.. From ft. to ft. ft. From to ft. From ft. **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite ft. Grout Intervals: 24 From ft.. From ft. ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit South How many feet? 12 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Τо O topsoil 30 clav <u> 30</u> medium sand 65 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 6/3/2015 and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp