WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SW 1/4 28 1/4 Т 27 S 2WF/W Distance and direction from nearest town or city street address of well if located within city? 1014 St Andrew Goddard, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10008 W. York ZIP CODE: 67215 Wichita, Kansas CITY, STATE: Application Number: 115 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: **ELEVATION** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 8/11/15 Pump test data: Well water was -NW NE ft. after hours of pumping @ gpm Est Yield: Well water was ft. after gpm hours of pumping @ gpm ≌ 12 Bore Hole Diameter to 115 and ft. WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well 5. Public water supply 1. Lawn and garden only SW SE-1. Domestic 3. Feedlot 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 2. PVC 4. ABS Asbestos-Cement 8. Concrete tile Blank casing diameter 35 ft., Dia. to in. to Dia ft. Casing height above land surface: in. Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2. Brass 4 Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 35 ft. 115 From ft., From to ft From ft. to ft., From ft. ft GRAVEL PACK INTERVALS: 24 ft. From to 115 ft., From ft. From to ft.. From ft to **GROUT MATERIALS:** 6 1. Neat cement Other 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 24 ft., From ft. ft... From ft What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 2. Sewer lines 5. Cess Pool 14. Abandon water well 3 Watertight sewer line 6 9. Feed yard 12. Fertilizer storage 6. Seepage pit How many feet? 20 ft. plus From LITHOLOGIC LOG Τо From Τо LITHOLOGIC LOG 0 3 topsoil 3 20 clav 20 39 medium sand 39 115 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and

was completed on (mo/day/year) 8-11-15 and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb