WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE 1/4 NW1/4 NW 1/4 13 Т 27 s R 2WΕ/W Distance and direction from nearest town or city street address of well if located within city? 1321 N. Forestview Ct. Wichita, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10008 W. York Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 4 DEPTH OF COMPLETED WELL: 70 ft **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: Ν WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm -NW NE-Est. Yield: gpm Well water was ft. after hours of pumping @ apm Ξ Bore Hole Diameter 12 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO S (YES) submitted Was Water Well Disinfected? NO TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS 5 50 ft., Blank casing diameter to ft.. Dia. in. Dia. ft. to in. to 12 2.35 Casing height above land surface: Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1 Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 2. Brass 4. Galvanized Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 3. Mill slot 5. Gauzed wrapped 7. Torch cut 11. None (open hole) 1. Continuous slot 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 50 70 From to ft., From ft. to ft. From to ft., From ft ft. to 24 **GRAVEL PACK INTERVALS:** to 70 From ft.. From ft. to ft. From ft. to ft.. From ft. to **GROUT MATERIALS:** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft. 24 ft., From ft. to ft.. From ft. What is the nearest source of possible contamination 10. Livestock pens 7. Pit privy 13. Insecticide storage 15 Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 6. Seepage pit Watertight sewer line North How many feet? 15 ft. plus Direction from well? From Τо LITHOLOGIC LOG From Τo LITHOLOGIC LOG 3 0 topsoil 35 3 clay 35 <u>45</u> fine sand 45 <u>70</u> medium sand under my jurisdiction and

7 Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under no was completed on (mo/day/year) 11/4/2015 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/5/15

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp