WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER LOCATION OF WATER WELL: FRACTION SW SE 27 Sedgwick NE 1/4 20 Т S 2WE/W Distance and direction from nearest town or city street address of well if located within city? 2023 N. Clearstone Ct. Goddard, Kansas NIEDENS, Karen WATER WELL OWNER: Board of Agriculture, Division of Water Resource 2911 N. Porter RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 116 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** WITH AN "X" IN SECTION BOX ft. Depth of groundwater Encountered: ft. 30 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/22/15 Pump test data: Well water was ft. after hours of pumping @ apm ΝW NE Well water was ft. after Φ Est. Yield: gpm hours of pumping @ gpm ≌ Bore Hole Diameter 12 116 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only  $X_{se}$ SW 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? CNO (YES) Was Water Well Disinfected? NO submitted TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 50 Dia. Blank casing diameter to Dia in. ft. in. to 2.35 12 in Weight: lbs. / ft. Wall thickness or gauge No. Casing height above land surface: .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 5. Gauzed wrapped 3. Mill slot 7. Torch cut 9. Drilled holes 11. None (open hole) 1 Continuous slot 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) 50 116 SCREEN - PERFORATION INTERVAL ft ft., From to From ft. ft to ft. From to ft., From ft. ft. to 24 GRAVEL PACK INTERVALS: ft. to 116 From ft., From ft. ft. ft. to ft.. From ft to ft. **GROUT MATERIALS** Other 6 bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 24 From ft From ft. to ft.. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? 10 ft. plus Direction from well? From From LITHOLOGIC LOG To LITHOLOGIC LOG Τo topsoil 18 clay 27 18 fine sand 27 116 grey shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and 10-22-2015 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief This water well record was completed on (mo/day/year) 10-23-2015 Kansas Water Well Contractor's License No. 236

by (signature)

under the business name of Harp Well and Pump Service

Todd S. Harb